IC697MDL740

DC Output Module

Sixteen-point 24/48 VDC output module with four fused groups of four outputs for higher-current field loads.

CATALOG
IC697MDL740

SIGNAL
24/48 VDC output

CHANNELS
16 points

POINT RATING
2 A maximum

FUNCTIONAL POSITION

01
PLC command

02
Output driver

03
Group fuse

04
24/48 VDC field load

APTER POWER / INDUSTRIAL AUTOMATION SUPPORT

+86 180 3023 5313 | WhatsApp / Phone

sales13@apterpower.com | www.apterpower.com

Verified capability map

OUTPUT GROUPING

Sixteen outputs arranged as four groups of four points.

VOLTAGE RANGE

20 to 60 VDC operating range; rated for 24 or 48 VDC.

LOAD CURRENT

2 A maximum per point and 4 A maximum per four-point group.

INRUSH

20 A maximum for 20 ms at an output point.

VOLTAGE DROP / LEAKAGE

0.8 V maximum output drop and 1 mA maximum output leakage.

RESPONSE

2 ms maximum ON response and 2 ms maximum OFF response.

FUSING

Each four-output group is protected by a 10 A fast-acting fuse.

BACKPLANE LOAD

0.15 A required from the 5 VDC backplane bus.

APTER POWER / INDUSTRIAL AUTOMATION SUPPORT

+86 180 3023 5313 | WhatsApp / Phone

sales13@apterpower.com | www.apterpower.com

Documented use and integration

01 PLC command – 02 Output driver – 03 Group fuse – 04 24/48 VDC field load

SOLENOID CONTROL

Drives documented DC solenoid circuits within the point and group current limits.

MOTOR STARTER COMMANDS

Provides controlled DC outputs to compatible starter or relay coils.

INDICATOR CIRCUITS

Switches documented 24 or 48 VDC annunciation and status loads.

HIGH-INRUSH DC LOADS

Supports short inrush events when repetition and group dissipation remain acceptable.

APTER POWER / INDUSTRIAL AUTOMATION SUPPORT

+86 180 3023 5313 | WhatsApp / Phone

sales13@apterpower.com | www.apterpower.com

Replacement and acceptance matrix

GATE 1

Verify IC697MDL740 and the documented hardware revision.

GATE 2

Archive output references and configured fault-state behavior.

GATE 3

Record every load, group common, polarity and fuse assignment.

GATE 4

Place controlled equipment in the approved safe state.

GATE 5

Isolate the rack and all field DC sources before removal.

GATE 6

Inspect or replace group fuses only with documented fast-acting types.

GATE 7

Energize under control and confirm diagnostics before commands.

GATE 8

Test all outputs under load and record the acceptance result.

APTER POWER / INDUSTRIAL AUTOMATION SUPPORT

+86 180 3023 5313 | WhatsApp / Phone

sales13@apterpower.com | www.apterpower.com

Sources, related pages and inquiry details

MANUFACTURER-AUTHORED SOURCE

GE Fanuc GFK-0086 / GFK-0600 Product Data

RELATED APTER POWER PRODUCTS

IC693PBS105

IC694MDL740

IC698CPE010

INQUIRY PACKAGE

Send the complete IC697MDL740 nameplate, quantity, condition preference, destination and required certificates for a model-controlled quotation.

APTER POWER / INDUSTRIAL AUTOMATION SUPPORT

+86 180 3023 5313 | WhatsApp / Phone

sales13@apterpower.com | www.apterpower.com