DI, 8-channel, 24 VDC isolated card

Emerson KJ3001X1-BA1 1290549X152 is a DeltaV DI, 8-channel, 24 VDC isolated card. The manufacturer instruction sheet defines its card function, power boundary, environmental ratings and keyed terminal-block interface for controlled installation and service.

- Eight isolated 24 VDC discrete-input channels
- 12 VDC LocalBus electronics supply
- Rotary-keyed I/O terminal-block interface
- Non-serviceable module with no field calibration

Field circuit

Documented signals and field power

KJ3001X1-BA1 1290549X152

DI, 8-channel, 24 VDC isolated card

DeltaV LocalBus

Controller communication and diagnostics

SYSTEM POSITION

The card occupies a keyed DeltaV I/O position between the LocalBus and the documented field circuit. Engineering acceptance depends on the exact KJ3001X1-BA1 1290549X152 marking, the matching terminal-block key, approved field wiring and the installed DeltaV hardware record.

IDENTITY HOLD POINT

Confirm the complete KJ3001X1-BA1 1290549X152 nameplate, installed terminal block, wiring diagram, field power and DeltaV cabinet record before removal, replacement or energization.

Card function	DI, 8-channel, 24 VDC, isolated
LocalBus power	12 VDC at 100 mA
Field circuit	24 VDC at 5 mA per channel
Ambient temperature	0 to +60 degrees C
Relative humidity	5 to 95% non-condensing; IP20 rating

INTEGRATION RECORD

Preserve the complete KJ3001X1-BA1 1290549X152 identity before replacement. Isolate field energy as required by the Emerson instruction sheet, verify the terminal-block key and wiring diagram, then confirm channel status and system diagnostics before returning the affected loops to service.

DOCUMENT CONTROL

Emerson Process Management ATEX Instruction Sheet D803021X012, KJ3001X1-BA1, February 2003

Shock	10 g half-sine for 11 ms
Vibration	1 mm peak-to-peak from 5 to 16 Hz; 0.5 g from 16 to 150 Hz
Airborne contaminants	ISA-S71.04-1985 Class G3
Terminal-block key	A4
Maintenance	No user-serviceable parts; no calibration

ENGINEERING NOTE

The exact sheet requires field-power removal before connection changes and gives conditional system-power insertion rules for one unit at a time with the specified dual DC/DC supply boundary. The exact KJ3001X1-BA1 card function is documented; the secondary identifier must be verified from the installed label because the manufacturer sheet does not decode every order-number revision.

DELTAV PROCESS I/O

Use the di, 8-channel, 24 vdc isolated card in the approved DeltaV I/O architecture with the exact keyed termination.

CABINET REPLACEMENT

Restore a documented installed position after identity, field energy, wiring and keying are verified.

How many isolated inputs does Emerson KJ3001X1-BA1 1290549X152 provide?

The KJ3001X1-BA1 manufacturer sheet identifies eight isolated 24 VDC discrete-input channels.

What LocalBus demand must the cabinet support for Emerson KJ3001X1-BA1 1290549X152?

The card electronics require 12 VDC at 100 mA from the LocalBus supply.

Which terminal-block key belongs with Emerson KJ3001X1-BA1 1290549X152?

The documented rotary-key position is A4, which must match the installed terminal block before insertion.

What field input applies per channel on Emerson KJ3001X1-BA1 1290549X152?

The exact card sheet lists a 24 VDC field circuit at 5 mA per channel.

When must field power be removed from Emerson KJ3001X1-BA1 1290549X152?

Field power must be removed before connecting or disconnecting the device.

Can Emerson KJ3001X1-BA1 1290549X152 be inserted with system power present?

Only the conditional one-unit insertion method and the specified dual DC/DC supply boundary in the manufacturer instruction may be used; otherwise system power must be de-energized.

What operating environment is documented for Emerson KJ3001X1-BA1 1290549X152?

The sheet lists 0 to +60 degrees C, 5 to 95% non-condensing relative humidity and an IP20 rating.

COMMISSIONING ACCEPTANCE

Preserve the complete KJ3001X1-BA1 1290549X152 identity before replacement. Isolate field energy as required by the Emerson instruction sheet, verify the terminal-block key and wiring diagram, then confirm channel status and system diagnostics before returning the affected loops to service.

RELEASE RECORD

Confirm the complete KJ3001X1-BA1 1290549X152 nameplate, installed terminal block, wiring diagram, field power and DeltaV cabinet record before removal, replacement or energization.

MANUFACTURER SOURCE

Emerson Process Management ATEX Instruction Sheet D803021X012, KJ3001X1-BA1, February 2003

Related Emerson catalog pages

Browse related automation products. These links do not establish interchangeability.

Emerson KJ3243X1-BK1 SE4022	View product
Emerson KJ4001X1-BA3 12P3378X012 VE3051C0	View product
Emerson KL2101X1-BA1 SE6501T01	View product

RELEASE BOUNDARY

Confirm the complete KJ3001X1-BA1 1290549X152 nameplate, installed terminal block, wiring diagram, field power and DeltaV cabinet record before removal, replacement or energization.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ3001X1-BA1 1290549X152