

1

01 Readiness and operating boundary

Siemens 6DD1683-0BC0 is the SIMADYN D SP8 power supply unit with a 24 V DC input. It supplies 5 V DC at 52 A and positive and negative 15 V rails for the configured rack, with forced cooling by an integrated fan.

Confirm exact identity

Read the full 6DD1683-0BC0 nameplate and confirm the SP8 designation.

Exact model	6DD1683-0BC0
Module designation	SP8
Hardware type	Power supply unit

Establish the safe work boundary

Verify the cabinet presents the documented 24 V DC feed with correct polarity.

Identity	6DD1683-0BC0
Host	SIMADYN D
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



6DD1683-0BC0

2 02 Configuration and interface setup

The SP8 converts the cabinet's 24 V DC feed into the logic and auxiliary rails required by its assigned SIMADYN D rack, so rack load, fan operation and rail stability are verified together.

Record the as-found configuration

Record rack population and estimated 5 V load before disturbing the supply.

Module designation	SP8
Hardware type	Power supply unit
Host platform	SIMADYN D

Map connections and settings

Isolate the rack and prove the input and stored-energy points safe.

Identity	6DD1683-0BC0
Host	SIMADYN D
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



6DD1683-0BC0

03 Installation and service sequence

The SP8 converts the cabinet's 24 V DC feed into the logic and auxiliary rails required by its assigned SIMADYN D rack, so rack load, fan operation and rail stability are verified together.

Restore the documented assembly

Inspect the fan path, connector condition and backplane mating surfaces.

Hardware type	Power supply unit
Host platform	SIMADYN D
Input	24 V DC

Protect every interface

Measure the 5 V, +15 V and -15 V rails after controlled energization.

Identity	6DD1683-0BC0
Host	SIMADYN D
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



6DD1683-0BC0

04 Verification and fault isolation

The SP8 converts the cabinet's 24 V DC feed into the logic and auxiliary rails required by its assigned SIMADYN D rack, so rack load, fan operation and rail stability are verified together.

Verify the installed function

Confirm fan operation and monitor the supply for abnormal heating or alarms.

Host platform	SIMADYN D
Input	24 V DC
Main output	5 V DC / 52 A

Isolate unexpected response

Release the rack only after processor and I/O startup diagnostics are normal.

Identity	6DD1683-0BC0
Host	SIMADYN D
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



6DD1683-0BC0

5 05 Acceptance and service handover

The SP8 converts the cabinet's 24 V DC feed into the logic and auxiliary rails required by its assigned SIMADYN D rack, so rack load, fan operation and rail stability are verified together.

Complete the release record

Read the full 6DD1683-0BC0 nameplate and confirm the SP8 designation.

Exact model	6DD1683-0BC0
Module designation	SP8
Hardware type	Power supply unit

Retain acceptance evidence

Verify the cabinet presents the documented 24 V DC feed with correct polarity.

Identity	6DD1683-0BC0
Host	SIMADYN D
Acceptance	Diagnostics and functional response

[Siemens 6ES7215 1BG40 0XB0 — View product page](#)

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



6DD1683-0BC0