APTER POWER / OFFICIAL MANUFACTURER REFERENCE

EPRO PR6423/13R-040 CON021

Selected official pages with exact-model applicability and related-model index

EXACT SCOPE

EPRO PR6423/13R-040 CON021 combines a reverse-mount armored PR6423 8 mm eddy-current sensor with a 10 m cable, Lemo converter connection and the compatible CON021 panel-mount signal converter. The matched system measures shaft displacement, position, eccentricity and speed-related events.

SOURCE SET

pr6423.pdf; con021.pdf

APPLICATION BOUNDARY

Use PR6423/13R-040 only with the documented connector and converter arrangement; do not transfer calibration data from a different PR6423 cable or mounting code.

RELATED MODELS


EPRO PR6423/002-000 CON021	Portfolio reference; verify every ordering field.
EPRO PR6423/003-030 CON021	Portfolio reference; verify every ordering field.
EPRO PR6423/015-040	Portfolio reference; verify every ordering field.
EPRO PR6423/018-040 CON021	Portfolio reference; verify every ordering field.
EPRO PR6423/018-140 CON021	Portfolio reference; verify every ordering field.
EPRO PR6424/014-140 CON021	Portfolio reference; verify every ordering field.

Connect with ApterPower


Phone: +86 180 3023 5313

Email: sales13@apterpower.com

8mm Eddy Current Sensor



Non-contact sensor designed for critical turbomachinery applications such as steam, gas and hydro turbines, compressors, gearboxes, pumps and fans to measure radial and axial shaft dynamic displacement; position, eccentricity and speed.



Performance	
Linear Measurement Range	2 mm (80 mils)
Initial Air Gap	0.5 mm (20 mils)
Incremental Scale Factor (ISF)	ISO: 8 V/mm (203.2 mV/mil) ± 5% @ temperature range 0 to 45°C (+32 to +113°F)
Deviation from best fit straight line (DSL)	± 0.025 mm (± 1 mil) @ temperature range 0 to 45°C (+32 to +113°F)
Measuring Target	
Minimum Shaft Diameter	25 mm (0.79”)
Target Material (Ferromagnetic Steel)	42CrMo4 (AISI/SAE 4140) Standard Other (On Request)
Environmental, General	
Protection Class	IP66, IEC 60529
Operating Temperature Range	Sensor incl. 1m Cable: -35 to +180°C (-31 to 356°F) Cable & Connector: -35 to +150°C (-31 to 302°F)
Material	Sensor Tip (PEEK Polyether Ether Ketone), Case (Stainless Steel) Cable (PTFE Polytetrafluoroethylene), Connector (Brass, nickel-plated)
Weight (Sensor with 1m Cable)	Approx. 100 grams (3.53 oz)

Compliance and Certifications	
CE	2014/30/EU (EN 61326-1) 2014/34/EU 2011/65/EU
ATEX	EN 60079-0 EN 60079-11
IEC-Ex	IEC 60079-0 IEC 60079-11 IEC 60079-26
CSA	CAN/CSA-C22.2 NO. 0-M91 CAN/CSA-C22.2 NO. 157-92 CAN/CSA-C22.2 NO. 213-M1987 CAN/CSA-E60079-15-02 (R2006) CAN/CSA-C22.2 NO. 25-1966 CAN/CSA-C22.2 NO. 61010-1-04 ANSI/UL Standard 913-2004 ANSI/UL Standard 1604-1995 UL 60079-15 2002 UL 61010-1

Hazardous Area Approvals

Intrinsic Safety (ia)	
ATEX / IEC-Ex / CSA	Area classification depends on converter, see converter documentation for details. Sensor temperature classification: T6: Ta ≤ 64°C T4: Ta ≤ 114°C T3: Ta ≤ 160°C
Non-sparking (nA)	
ATEX / IEC-Ex / CSA	Area classification depends on converter, see converter documentation for details. Sensor temperature classification: T6: Ta ≤ 64°C T4: Ta ≤ 114°C T3: Ta ≤ 160°C

Ordering Information

Tip Diameter	Case Threads	Armored Cable	Model No.
8mm	M10x1	No	PR6423/00
		Yes	PR6423/01
			PR6423/03*
	3/8"-24 UNF	No	PR6423/10
		Yes	PR6423/11
			PR6423/13*

**Armored cable option for Reverse Mount, if Adapter Plug is chosen.*

Model No.	Case Thread X	Adapter Plug X	Cable Length X	Cable End X
PR6423/00 PR6423/01 PR6423/10 PR6423/11	**0** 25mm **1** 35mm **2** 45mm **3** 55mm **4** 65mm **5** 75mm **6** 85mm **7** 95mm **8** 105mm **9** 115mm **E** 155mm **H** 195mm **R** Reverse Mount	**0** With **1** Without	**0** 4.0m **1** 5.0m **3** 8.0m **F** 9.0m **4** 10.0m	**0** Lemo* **1** Open

**Not available, if Reverse Mount without Adapter Plug is chosen.*

Example: PR6423/000-000

ECS 8mm, M10X1, NO ARMOR, 25MM SLEEVE, 1+3M CABLE, LEMO

Ordering Information

Model Number	Sensor Type	Measuring Range	Linearity Error
CON021	PR6422 PR6423 PR6424 PR6426	1.0mm (Standard Range) 2.0mm (Standard Range) 4.0mm (Standard Range) 8.0mm (Standard Range)	≤ 1.5% ≤ 1.0% ≤ 1.5% ≤ 1.5%
CON021/912-015	PR6422	1.5mm (Extended Range)	≤ 2.0%
CON021/913-030	PR6423	3.0mm (Extended Range)	≤ 1.5%
CON021/913-040	PR6423	4.0mm (Extended Range)	≤ 2.0%
CON021/914-060	PR6424	6.0mm (Extended Range)	≤ 1.0%
CON021/914-080	PR6424	8.0mm (Extended Range)	≤ 1.5%
CON021/914-100	PR6424	10.0mm (Extended Range)	≤ 2.0%
CON021/915-040	PR6425	4.0mm (Standard Range)	≤ 1.5%
CON021/915-060	PR6425	6.0mm (Extended Range)	≤ 2.0%
CON021/915-080	PR6425	8.0mm (Extended Range)	≤ 3.0%
CON021/915-100	PR6425	10.0mm (Extended Range)	≤ 4.0%
CON021/916-120	PR6426	12.0mm (Extended Range)	≤ 1.5%
CON021/916-160	PR6426	16.0mm (Extended Range)	≤ 2.0%
CON021/916-200	PR6426	20.0mm (Extended Range)	≤ 2.5%
CON021/916-240	PR6426	24.0mm (Extended Range)	≤ 3.5%

Emerson
Reliability Solutions
835 Innovation Drive
Knoxville, TN 37932 USA
+1 865 675 2400

www.emerson.com/ams

©2017, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.