330101-00-08-05-02-00, 330101-00-08-05-02-05, 330101-00-08-10-02-00, 330101-00-08-10-02-05, 330101-00-12-10-02-00, 330101-00-12-10-02-05, 330101-00-16-10-02-00, 330101-00-16-10-02-05, 330101-00-20-05-02-00, 330101-00-20-10-02-00, 330101-00-20-10-02-05, 330101-00-30-10-02-00, 330101-00-30-10-02-05, 330101-00-40-05-02-00, 330101-00-40-10-02-00, 330101-00-40-10-02-05, 330101-00-60-10-02-00, 330101-00-60-10-02-05, 330102-00-20-10-02-00, 330103-00-02-10-02-05, 330103-00-04-10-02-00, 330103-00-05-10-02-00, 330104-00-06-10-02-00, 330104-01-05-50-02-00, 330105-02-12-05-02-00, 330105-02-12-05-02-05, 330105-02-12-10-02-00, 330105-02-12-10-02-05, 330106-05-30-05-02-00, 330106-05-30-05-02-05, 330106-05-30-10-02-00, 330106-05-30-10-02-05.

## Ordering Information for Proximitor Sensor

### 3300 XL Proximitor Sensor

**330180-AA-BB**

| **A: Total Length and Mounting Option** | |
|---|---|
| **10** | 1.0 meter (3.3 feet) system length, panel mount |
| **11** | 1.0 meter (3.3 feet) system length, DIN mount |
| **12** | 1.0 meter (3.3 feet) system length, no mounting hardware |
| **50** | 5.0 meters (16.4 feet) system length, panel mount |
| **51** | 5.0 meters (16.4 feet) system length, DIN mount |
| **52** | 5.0 meters (16.4 feet) system length, no mounting hardware |
| **90** | 9.0 meters (29.5 feet) system length, panel mount |
| **91** | 9.0 meters (29.5 feet) system length, DIN mount |
| **92** | 9.0 meters (29.5 feet) system length, no mounting hardware |
| **B: Agency Approval Option** | |
| **00** | Not required |
| **05** | CSA, ATEX, IECEx Approvals |

## Ordering Information for Extension Cables

### 3300 XL Standard Extension Cable

**330130-AAA-BB-CC**

Make sure that the extension cable length and the probe length, when added together, equal the Proximitor Sensor total length.

| **A: Cable Length Option** | |
|---|---|
| **030** | 3.0 meters (9.8 feet) |
| **035** | 3.5 meters (13.1 feet) |
| **040** | 4.0 meters (11.5 feet) |
| **045** | 4.5 meters (14.8 feet) |
| **060** | 6.0 meters (19.7 feet) |
| **070** | 7.0 meters (22.9 feet) |
| **075** | 7.5 meters (24.6 feet) |
| **080** | 8.0 meters (26.2 feet) |
| **085** | 8.5 meters (27.9 feet) |
| **B: Connector Protector and Cable Option** | |
| **00** | Standard cable |
| **01** | Armored cable |
| **02** | Standard cable with connector protector |

| | |
|---|---|
| **03** | Armored cable with connector protector |
| **10** | FluidLoc cable |
| **11** | Armored FluidLoc cable |
| **12** | FluidLoc cable with connector protector |
| **13** | Armored FluidLoc cable with connector protector |
| **C: Agency Approval Option** | |
| **00** | Not required |
| **05** | CSA, ATEX, IECEx Approvals |

## 3300 XL Extended Temperature Range (ETR) Extension Cable

**330190-AAA-BB-CC**

Make sure that the extension cable length and the probe length, when added together, equal the Proximitor Sensor total length.

| | |
|---|---|
| **A: Cable Length Option** | |
| **030** | 3.0 meters (9.8 feet) |
| **035** | 3.5 meters (13.1 feet) |
| **040** | 4.0 meters (11.5 feet) |
| **045** | 4.5 meters (14.8 feet) |
| **070** | 7.0 meters (22.9 feet) |
| **075** | 7.5 meters (24.6 feet) |
| **080** | 8.0 meters (26.2 feet) |
| **085** | 8.5 meters (27.9 feet) |
| **B: Cable Option** | |
| **00** | Standard cable |
| **01** | Armored cable |
| **C: Agency Approval Option** | |
| **00** | Not required |
| **05** | CSA, ATEX, IECEx Approvals |

## Accessories

| | |
|---|---|
| 141078 | 3300 XL 8 mm and 3300 5 mm Proximity Transducer System Manual. |
| 175751 | 3300 XL Multi-Purpose Stainless Steel Housing. 12”x12”x6”. Can hold up to 8 Proximitor Sensors in a DIN-mount configuration or 6 Proximitor Sensors in a panel-mount configuration. (Available with ATEX/IECEx Zone 2 type << u >> certifications). |
| 176467 | 3300 XL Multi-Purpose Stainless Steel Housing. 12”x8”x6”. Can hold up to 4 3300XL Proximitor Sensors in both DIN-mount and panel-mount configurations. (Available with ATEX/IECEx Zone 2 type << u >> certifications). |
| 330181 | 3300 XL Multi-Purpose Stainless Steel Housing. 13”x9.5”x7”. Can hold up to 8 Proximitor sensors in a DIN-mount configuration or 6 Proximitor Sensors in a panel-mount configuration. Primarily used by customers requiring hazardous area approvals fro their installations. Available with North American type 4x certification suitable for installation in Div 2. |
| 02120015 | Bulk field wire. 1.0 mm2 (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet. |
| 138492-01 | Replacement panel-mount mounting pad. |
| 138493-01 | Replacement DIN-mount mounting pad. |