1

01 Readiness and operating boundary

Siemens RD63F200 is the frame-only component for a three-pole RD6 molded-case circuit breaker assembly in the 2000 A row. It is used with the specified trip unit, mounting assembly and lug set to build the complete protection device.

Confirm exact identity

Confirm the complete RD63F200 frame identity and the installed RD6 three-pole assembly before work.

Exact article	US2:RD63F200
Product type	RD6 frame only
Poles	3

Establish the safe work boundary

De-energize, lock out and prove every source and load conductor safe before opening the breaker assembly.

Identity	RD63F200
Host	RD6 molded-case circuit breaker system
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

RD63F200

2

02 Configuration and interface setup

In an RD6 distribution assembly, Siemens RD63F200 provides the frame for the 600 V AC interchangeable-trip breaker architecture; selection depends on the matching 2000 A trip, mounting base and conductor terminals.

Record the as-found configuration

Match the RD63T200 trip unit and its 2000 A setting range to the retained protection study and coordination record.

Product type	RD6 frame only
Poles	3
Frame rating row	2000 A at 40 degrees C

Map connections and settings

Restore the specified MB9301 or MBR9302 mounting assembly without changing the documented access arrangement.

Identity	RD63F200
Host	RD6 molded-case circuit breaker system
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

RD63F200

3

03 Installation and service sequence

In an RD6 distribution assembly, Siemens RD63F200 provides the frame for the 600 V AC interchangeable-trip breaker architecture; selection depends on the matching 2000 A trip, mounting base and conductor terminals.

Restore the documented assembly

Install six TC5R600 lugs and accept only the documented 300-600 kcmil copper conductor range and cable count.

Poles	3
Frame rating row	2000 A at 40 degrees C
AC rating	600 V AC

Protect every interface

Verify that available fault current does not exceed the documented interrupting rating at the actual system voltage.

Identity	RD63F200
Host	RD6 molded-case circuit breaker system
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

RD63F200

4

04 Verification and fault isolation

In an RD6 distribution assembly, Siemens RD63F200 provides the frame for the 600 V AC interchangeable-trip breaker architecture; selection depends on the matching 2000 A trip, mounting base and conductor terminals.

Verify the installed function

Use only the documented two-pole 250 V DC or three-pole 500 V DC arrangement when the application is direct current.

Frame rating row	2000 A at 40 degrees C
AC rating	600 V AC
Trip construction	Interchangeable

Isolate unexpected response

Complete mechanical, insulation, trip, contact and controlled energization checks before returning the breaker to service.

Identity	RD63F200
Host	RD6 molded-case circuit breaker system
Acceptance	Diagnostics and functional response

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

RD63F200

5

05 Acceptance and service handover

In an RD6 distribution assembly, Siemens RD63F200 provides the frame for the 600 V AC interchangeable-trip breaker architecture; selection depends on the matching 2000 A trip, mounting base and conductor terminals.

Complete the release record

Confirm the complete RD63F200 frame identity and the installed RD6 three-pole assembly before work.

Exact article	US2:RD63F200
Product type	RD6 frame only
Poles	3

Retain acceptance evidence

De-energize, lock out and prove every source and load conductor safe before opening the breaker assembly.

Identity	RD63F200
Host	RD6 molded-case circuit breaker system
Acceptance	Diagnostics and functional response

Siemens 6EP1961-3BA21 Power Supply Accessory

Siemens 3TY7540-0A Switching Accessory

Siemens A5E02822120 Power Component

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

RD63F200