1

01 Readiness and operating boundary

Reconcile the complete item marking with the receiving position and capture the as-found installation before isolation.

Capture the installed identity

Confirm the complete Emerson KJ4001X1-NB1 12P3368X022 marking against the receiving record before work.

Complete item marking	KJ4001X1-NB1 12P3368X022
Documented base model	KJ4001X1-NB1
Documented position	Left LocalBus extender, one-wide

Prove the work boundary

Place the connected process, rack, machinery and control functions in the approved maintenance state.

Identity	KJ4001X1-NB1 12P3368X022
Host	DeltaV M-series
Acceptance	Isolation and label record

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ4001X1-NB1 12P3368X022

2

02 Configuration and interface setup

Convert retained records into a controlled map of power, signal, communication, terminal and configuration interfaces.

Build the channel map

Record the installed position, wiring, terminal hardware, settings and companion components before removal.

Documented base model	KJ4001X1-NB1
Documented position	Left LocalBus extender, one-wide
LocalBus rating	12 V DC, 8 A

Classify every field circuit

Create a point-by-point map of every affected connector, terminal, channel, address and setting.

Identity	KJ4001X1-NB1 12P3368X022
Host	DeltaV M-series
Acceptance	Channel map approved

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ4001X1-NB1 12P3368X022

3

03 Installation and service sequence

Install the exact hardware identity and rebuild each interface without altering the approved architecture.

Restore the physical assembly

Isolate every affected electrical and process-energy source and verify the safe state.

Documented position	Left LocalBus extender, one-wide
LocalBus rating	12 V DC, 8 A
Operating temperature	-40 to 70°C

Apply controlled settings

Protect keyed connectors, terminals and electronics from contamination, strain and electrostatic damage.

Identity	KJ4001X1-NB1 12P3368X022
Host	DeltaV M-series
Acceptance	Assembly and settings restored

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ4001X1-NB1 12P3368X022

4

04 Verification and fault isolation

Energize under controlled conditions and observe every available module, rack, process and system diagnostic.

Observe supervised states

Restore only the recorded wiring, grounding, shielding, settings and matched companion hardware.

LocalBus rating	12 V DC, 8 A
Operating temperature	-40 to 70°C
Storage temperature	-40 to 85°C

Exercise fault indications

Energize in the controlled sequence and review every available module, rack and system diagnostic.

Identity	KJ4001X1-NB1 12P3368X022
Host	DeltaV M-series
Acceptance	Supervision response recorded

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ4001X1-NB1 12P3368X022

5

05 Acceptance and service handover

Release the equipment only after identity, installation and functional evidence are recorded together.

Compile the acceptance package

Function-test left-hand LocalBus extension and retain the signed acceptance result before service release.

Complete item marking	KJ4001X1-NB1 12P3368X022
Documented base model	KJ4001X1-NB1
Documented position	Left LocalBus extender, one-wide

Authorize the handover

Attach the as-left diagnostic state and named release owner to the handover record.

Identity	KJ4001X1-NB1 12P3368X022
Host	DeltaV M-series
Acceptance	Release evidence complete

Emerson PR9376-010-011

Emerson PR9350-02-S2

Emerson A6220

CONTACT APTER POWER

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

KJ4001X1-NB1 12P3368X022