

1

01 Readiness and operating boundary

Reconcile the complete item marking with the receiving position and capture the as-found installation before isolation.

Capture the installed identity

Confirm the complete Emerson KJ4001X1-CJ1 12P1902X042 marking against the receiving record before work.

Complete item marking	KJ4001X1-CJ1 12P1902X042
Documented base model	KJ4001X1-CJ1
Documented function	32-channel terminal block

Prove the work boundary

Place the connected process, rack, machinery and control functions in the approved maintenance state.

Identity	KJ4001X1-CJ1 12P1902X042
Host	DeltaV M-series
Acceptance	Isolation and label record

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



KJ4001X1-CJ1 12P1902X042

2 02 Configuration and interface setup

Convert retained records into a controlled map of power, signal, communication, terminal and configuration interfaces.

Build the channel map

Record the installed position, wiring, terminal hardware, settings and companion components before removal.

Documented base model	KJ4001X1-CJ1
Documented function	32-channel terminal block
Maximum input rating	30 V DC, 1 A

Classify every field circuit

Create a point-by-point map of every affected connector, terminal, channel, address and setting.

Identity	KJ4001X1-CJ1 12P1902X042
Host	DeltaV M-series
Acceptance	Channel map approved

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



KJ4001X1-CJ1 12P1902X042

3

03 Installation and service sequence

Install the exact hardware identity and rebuild each interface without altering the approved architecture.

Restore the physical assembly

Isolate every affected electrical and process-energy source and verify the safe state.

Documented function	32-channel terminal block
Maximum input rating	30 V DC, 1 A
Operating temperature	-40 to 70°C

Apply controlled settings

Protect keyed connectors, terminals and electronics from contamination, strain and electrostatic damage.

Identity	KJ4001X1-CJ1 12P1902X042
Host	DeltaV M-series
Acceptance	Assembly and settings restored

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



KJ4001X1-CJ1 12P1902X042

04 Verification and fault isolation

Energize under controlled conditions and observe every available module, rack, process and system diagnostic.

Observe supervised states

Restore only the recorded wiring, grounding, shielding, settings and matched companion hardware.

Maximum input rating	30 V DC, 1 A
Operating temperature	-40 to 70°C
Storage temperature	-40 to 85°C

Exercise fault indications

Energize in the controlled sequence and review every available module, rack and system diagnostic.

Identity	KJ4001X1-CJ1 12P1902X042
Host	DeltaV M-series
Acceptance	Supervision response recorded

PAGE TRACE	REQUIRED ENTRY
Inspector	_____
Result	Pass / hold / corrective action
Record	Date, diagnostic state and release reference

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



KJ4001X1-CJ1 12P1902X042

5 05 Acceptance and service handover

Release the equipment only after identity, installation and functional evidence are recorded together.

Compile the acceptance package

Function-test 32-channel field termination and retain the signed acceptance result before service release.

Complete item marking	KJ4001X1-CJ1 12P1902X042
Documented base model	KJ4001X1-CJ1
Documented function	32-channel terminal block

Authorize the handover

Attach the as-left diagnostic state and named release owner to the handover record.

Identity	KJ4001X1-CJ1 12P1902X042
Host	DeltaV M-series
Acceptance	Release evidence complete

Emerson KJ4010X1-BG1 12P0830X062

Emerson KJ4010X1-BG1 12P0830X072

Emerson VE4003S5B1 KJ3002X1-BG2 12P1731X082

CONTACT APTER POWER

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com



KJ4001X1-CJ1 12P1902X042