

Westinghouse 1C31125G02

Complete Product Information

Westinghouse 1C31125G02 connects the sixteen-channel Ovation digital-output electronics module to locally powered relay modules or directly to field terminal blocks.

WHAT THIS PRODUCT DOES

Westinghouse 1C31125G02 serves as a digital output personality module in the Ovation I/O subsystem. It interfaces digital output or relay-panel interface with 1C31122G01 digital-output electronics module and locally powered relay hardware.

Product characteristic 1 Provides sixteen output paths for the documented digital output personality module function.	Product characteristic 2 Handles digital output or relay-panel interface through the specified Ovation I/O subsystem.
Product characteristic 3 Works with 1C31122G01 digital-output electronics module and locally powered relay hardware.	Product characteristic 4 Local auxiliary power is used when the personality module interfaces the electronics module to relay modules.

PRODUCT-PAGE TECHNICAL SNAPSHOT

Subsystem	0-60 V dc digital output
Channels	16
Electronics module	1C31122G01
Relay power	Local I/O-backplane auxiliary power

IMPORTANT NOTICE	Use 1C31125G02 only with 1C31122G01 digital-output electronics module and locally powered relay hardware; verify the field interface and controlled configuration before energizing the subsystem.
-------------------------	--

APTERPOWER SALES TEAM
WhatsApp / Phone: +86 180 3023 5313
Email: sales13@apterpower.com
Scan the approved WhatsApp code for model-specific support.



Features and technical data

TECHNICAL DATA SHOWN ON THE PRODUCT PAGE

Subsystem	0-60 V dc digital output
Channels	16
Electronics module	1C31122G01
Relay power	Local I/O-backplane auxiliary power
Field option	May also route outputs through terminal blocks

FEATURE INTERPRETATION

Product identity Provides sixteen output paths for the documented digital output personality module function.	System role Handles digital output or relay-panel interface through the specified Ovation I/O subsystem.
Service context Works with 1C31122G01 digital-output electronics module and locally powered relay hardware.	Return-to-service focus Local auxiliary power is used when the personality module interfaces the electronics module to relay modules.

SIGNAL OR CONTROL PATH



The digital output personality module belongs in the controlled Ovation I/O subsystem and works with 1C31122G01 digital-output electronics module and locally powered relay hardware. Its field connection, companion hardware and project configuration must be reviewed together before the channel is returned to service.

PRODUCT-PAGE TECHNICAL QUESTIONS

What function does Westinghouse 1C31125G02 perform?	It connects the sixteen-channel Ovation digital-output electronics module to locally powered relay modules or directly to field terminal blocks.
How many channels are associated with Westinghouse 1C31125G02?	The documented configuration provides sixteen output paths.
Which signal path is used by Westinghouse 1C31125G02?	It is used for digital output or relay-panel interface within the specified subsystem.

Common applications

The application groups below reproduce the model-specific uses presented on the product page and connect each use to a practical verification point.

Installed-base maintenance Restores the documented digital output personality module position without changing the approved system architecture.	Loop or channel service Supports verification of digital output or relay-panel interface at the assigned control-system channel.
Planned replacement Provides an exact-identity replacement path when 1C31122G01 digital-output electronics module and locally powered relay hardware and the field interface have been confirmed.	Commissioning support Allows the responsible engineer to prove wiring, configuration, status and response for sixteen output paths.

APPLICATION VERIFICATION MAP

Installed-base maintenance	Confirm the documented system position and the required operating function.
Loop or channel service	Compare the restored connection or control path with the approved record.
Planned replacement	Check the physical interface and the retained configuration before startup.
Commissioning support	Record diagnostics and the final controlled response before release.

INFORMATION CARRIED INTO THE WORK RECORD

Identity record Complete marking and assigned system position.	Connection record Connector, conductor and interface arrangement as found.
Configuration record Controlled settings, application data and option state.	Acceptance record Observed status, response and release decision.

IMPORTANT NOTICE

Use the complete product identifier for every application review; a related product link is not evidence of interchangeability.

APPLICATION QUESTIONS

Which signal path is used by Westinghouse 1C31125G02?	It is used for digital output or relay-panel interface within the specified subsystem.
Which companion hardware must be checked for Westinghouse 1C31125G02?	Confirm 1C31122G01 digital-output electronics module and locally powered relay hardware and the project-specific base or terminal arrangement.
What technical values should be verified before installing Westinghouse 1C31125G02?	Verify 0-60 V dc digital output; also confirm 16 and every applicable range or wiring selection.

Product precautions and questions

EIGHT MODEL-SPECIFIC PRECAUTIONS

- 01 Match the complete 1C31125G02 marking to the work order and installed position before removal.
- 02 Confirm 1C31122G01 digital-output electronics module and locally powered relay hardware before making or breaking any field connection.
- 03 Keep the assigned digital output or relay-panel interface within the documented subsystem and range.
- 04 Record terminal designations, polarity, common and shield treatment before disconnecting conductors.
- 05 Inspect module seating, connector keying, terminal condition and strain relief before power is restored.
- 06 Restore the controlled channel configuration, range selection and alarm or timeout behavior after installation.
- 07 Check local indicators and controller diagnostics for internal, communication or channel faults during commissioning.
- 08 Prove the intended response across sixteen output paths and record the acceptance result before release.

FREQUENTLY ASKED TECHNICAL QUESTIONS

What function does Westinghouse 1C31125G02 perform?	It connects the sixteen-channel Ovation digital-output electronics module to locally powered relay modules or directly to field terminal blocks.
How many channels are associated with Westinghouse 1C31125G02?	The documented configuration provides sixteen output paths.
Which signal path is used by Westinghouse 1C31125G02?	It is used for digital output or relay-panel interface within the specified subsystem.
Which companion hardware must be checked for Westinghouse 1C31125G02?	Confirm 1C31122G01 digital-output electronics module and locally powered relay hardware and the project-specific base or terminal arrangement.

IMPORTANT NOTICE

Use 1C31125G02 only with 1C31122G01 digital-output electronics module and locally powered relay hardware; verify the field interface and controlled configuration before energizing the subsystem.

RELEASE CHECKLIST

Identity accepted	The complete product marking and assigned system position agree.
Interfaces accepted	Connections, retention and controlled configuration match the recorded condition.
Response accepted	Diagnostics and the intended technical response have been documented.

FAQ, source record and related models

ADDITIONAL TECHNICAL QUESTIONS

What technical values should be verified before installing Westinghouse 1C31125G02?	Verify 0-60 V dc digital output; also confirm 16 and every applicable range or wiring selection.
What connection details should be recorded for Westinghouse 1C31125G02?	Record terminal identifiers, polarity, common, shield termination, connector keying and the assigned channel before disconnection.
Which diagnostics should be reviewed when commissioning Westinghouse 1C31125G02?	Review the applicable power, communication, internal-fault and channel-status indications, then compare the controller status with the expected field condition.
Can a nearby ordering code replace Westinghouse 1C31125G02 without an engineering check?	No. Match the complete identifier, companion hardware, signal range, wiring and controlled project configuration before substitution.

MANUFACTURER EVIDENCE RECORD

Manufacturer source	Emerson Process Management, Ovation I/O Reference Manual R3-1150 Rev 3, Section 12, February 2003.
Evidence boundary	Technical statements are limited to the identified product or applicable manufacturer family.
Selection control	Use the complete ordering string and verify the installed system before purchase or installation.

RELATED MODELS ON APTERPOWER

Westinghouse 5X00121G01	Related product reference. Review the complete ordering string before selection.
Foxboro AD908AA FBM201	Related product reference. Compare the required interface and system position.
Foxboro AD916AG FBM204	Related product reference. Confirm the execution independently for the intended task.

APTERPOWER SALES TEAM
 WhatsApp / Phone: +86 180 3023 5313
 Email: sales13@apterpower.com
 Scan the approved WhatsApp code for model-specific support.

