GE DS200SHVMG1AED

Technical Reference

GE DS200SHVMG1AED is a high voltage interface board identified for service in a matched legacy GE control assembly; the complete suffix must be retained during replacement.

PRODUCT ROLE AND TECHNICAL FEATURES

Feature 1

Uses the DS200 board-family identification.

Feature 2

Provides high-voltage interface functions in the installed control assembly.

Feature 3

Retains the complete suffix as part of the replacement identity.

Feature 4

Requires the original connector, slot and wiring relationship to be preserved.

TECHNICAL DATA SNAPSHOT

Product form	Printed circuit board assembly
Platform family	DS200
Functional area	High-voltage interface functions
Installation position	Matched existing board position

SYSTEM RELATIONSHIP

Field device → **Product interface** → **System channel** → **Verified response**

APTERPOWER SALES TEAM
WhatsApp / Phone: +86 180 3023 5313
Email: sales13@apterpower.com
Scan the approved WhatsApp code for model-specific support.

Technical profile

Technical values for the complete product string are arranged below for selection and engineering review.

Product form	Printed circuit board assembly
Platform family	DS200
Functional area	High-voltage interface functions
Installation position	Matched existing board position
Connection basis	Existing harnesses, connectors and backplane interfaces
Identity control	Complete catalog number and suffix required
Replacement method	Like-for-like controlled substitution
Commissioning basis	System diagnostics and affected-circuit functional checks

SELECTION ANCHORS

- Uses the DS200 board-family identification.
- Provides high-voltage interface functions in the installed control assembly.
- Retains the complete suffix as part of the replacement identity.
- Requires the original connector, slot and wiring relationship to be preserved.

IMPORTANT NOTICE	Use the values as one matched configuration. Do not substitute a nearby ordering code without a separate check.

MANUFACTURER DOCUMENT REFERENCE

Manufacturer document	Exact product marking and verified GE board-family/document references available for this legacy assembly.
Application scope	The values below apply to the identified product and its documented system relationship.
Selection rule	Use the complete ordering string and confirm the installed interfaces before selection.

ADDITIONAL ENGINEERING CHECKS

Which checks should follow installation of GE DS200SHVMG1AED?	Run the affected controller or drive diagnostics, verify connected circuits and confirm the expected system response.
When should GE DS200SHVMG1AED be returned to service?	Release the equipment only after connector security, configuration records and all affected functional checks are complete.

System role and architecture

Field device → Product interface → System channel → Verified response

APPLICATION POINTS

Controlled board replacement

Restores the documented board position after the installed identity and interfaces are matched.

Legacy control maintenance

Supports service work on equipment using the DS200 board family.

Interface-path recovery

Returns the affected high-voltage interface functions after connector and wiring checks.

Diagnostic troubleshooting

Provides a defined replacement point when system tests isolate the fault to this board assembly.

INTEGRATION RECORD

Identity	Record the complete marking and installed position.
Mechanical interface	Confirm mounting, support, clearance and connector engagement.
Electrical interface	Confirm signal path, shield, common and receiving-channel assignment.
Configuration	Retain the controlled channel settings and acceptance criteria.
Functional result	Record the expected static value, dynamic response and system status.

GE DS200SHVMG1AED should be matched to the removed board by full marking, connector layout, installed location and system documentation before any wiring is transferred.

ENGINEERING REVIEW QUESTIONS

What equipment identity must be matched before installing GE DS200SHVMG1AED?	Match the complete DS200SHVMG1AED marking, board position, connector pattern and installed-system documentation.
Why is the suffix important on GE DS200SHVMG1AED?	The suffix is part of the complete board identity and should be preserved during like-for-like replacement.
Which connections should be recorded before GE DS200SHVMG1AED is removed?	Record every plug, keyed connector, jumper, cable label, shield and terminal relationship associated with the installed board.
How should GE DS200SHVMG1AED be handled during service?	Use approved ESD handling and support the board by its edges without loading components or connector pins.

Engineering checks and acceptance

PRODUCT PRECAUTIONS

01	Confirm the complete DS200SHVMG1AED marking before removing the installed board.
02	De-energize the equipment and follow the approved stored-energy procedure.
03	Photograph and label every connector, jumper and cable before disconnection.
04	Use ESD controls when handling the printed circuit board assembly.
05	Inspect connector keys, edge contacts and card guides before insertion.
06	Do not transfer jumpers or configurable devices until their original positions are recorded.
07	Restore every harness and shield to the documented termination point.
08	Run the affected system diagnostics and functional checks before release.

RELEASE CHECKS

Exact identity	Product marking and intended system position agree.
Interface condition	Mounting, connectors, terminals and cable routing are secure.
Signal response	The expected static and dynamic behavior has been observed.
Protection state	Channel status, alarms and controlled bypass state are restored.

IMPORTANT NOTICE	Match the complete DS200SHVMG1AED identity and installed interfaces before replacement.

APPLICATION BOUNDARIES

Controlled board replacement	Restores the documented board position after the installed identity and interfaces are matched.
Legacy control maintenance	Supports service work on equipment using the DS200 board family.
Interface-path recovery	Returns the affected high-voltage interface functions after connector and wiring checks.
Diagnostic troubleshooting	Provides a defined replacement point when system tests isolate the fault to this board assembly.

Technical questions and related models

MODEL-SPECIFIC QUESTIONS

What equipment identity must be matched before installing GE DS200SHVMG1AED?	Match the complete DS200SHVMG1AED marking, board position, connector pattern and installed-system documentation.
Why is the suffix important on GE DS200SHVMG1AED?	The suffix is part of the complete board identity and should be preserved during like-for-like replacement.
Which connections should be recorded before GE DS200SHVMG1AED is removed?	Record every plug, keyed connector, jumper, cable label, shield and terminal relationship associated with the installed board.
How should GE DS200SHVMG1AED be handled during service?	Use approved ESD handling and support the board by its edges without loading components or connector pins.
What should be inspected before seating GE DS200SHVMG1AED?	Inspect card guides, connector keys, mating contacts, harness condition and the intended board position.
Can GE DS200SHVMG1AED be substituted using only a shortened base number?	No. Use the complete catalog string and confirm the installed interfaces before substitution.

RELATED MODELS ON APTERPOWER

GE 531X304IBDANG1 F31X304IBDAMG1	Related product reference. Review the complete ordering string before selection.
GE DS200ADPBG1ABB	Related product reference. Compare the required interface and system position.
GE DS200LDCCH1ALA DS200LDCCH1	Related product reference. Confirm the execution independently for the intended task.

DOCUMENT AND SELECTION RECORD

Manufacturer document	Exact product marking and verified GE board-family/document references available for this legacy assembly.
Application scope	The values below apply to the identified product and its documented system relationship.
Selection rule	Use the complete ordering string and confirm the installed interfaces before selection.

APTERPOWER SALES TEAM
WhatsApp / Phone: +86 180 3023 5313
Email: sales13@apterpower.com
Scan the approved WhatsApp code for model-specific support.