Siemens 405-4DAC-1
Complete Product Information

PRODUCT OVERVIEW

Product	405-4DAC-1
Type	4-Channel Analog Output Module
Platform	SIMATIC TI 405
Primary role	four-channel analog output module

KEY CAPABILITIES

Capability 1 Provides the four-channel analog output module function.	Capability 2 Integrates with the SIMATIC TI 405 platform.
Capability 3 Retains the assigned signal or communication path.	Capability 4 Uses the complete 405-4DAC-1 identity for replacement control.

WHERE IT FITS

Installed-base maintenance Restore the assigned four-channel analog output module position without changing the surrounding system design.	Loop and channel service Retain terminal assignments, scaling and channel ownership during controlled replacement.
Fault isolation Separate module, field wiring and configuration causes during troubleshooting.	Commissioning Prove the complete signal path before returning the process to service.

ApterPower product support
Scan for model-specific assistance.

Capabilities at a glance

PRODUCT PARAMETERS

Output channels	4
Resolution	12 bit
Current range	4 to 20 mA
Voltage ranges	0 to 5 V; 0 to 10 V
System family	SIMATIC TI 405
Connection control	Match installed terminals
Configuration basis	Preserve assigned settings
Acceptance focus	Confirm end-to-end response

CAPABILITY INTERPRETATION

Capability 1	Provides the four-channel analog output module function. This supports the assigned SIMATIC TI 405 maintenance strategy.
Capability 2	Integrates with the SIMATIC TI 405 platform. This supports the assigned SIMATIC TI 405 maintenance strategy.
Capability 3	Retains the assigned signal or communication path. This supports the assigned SIMATIC TI 405 maintenance strategy.
Capability 4	Uses the complete 405-4DAC-1 identity for replacement control. This supports the assigned SIMATIC TI 405 maintenance strategy.

SYSTEM RELATIONSHIP

Upstream Field source or system command assigned to the four-channel analog output module function.	Product role 405-4DAC-1 performs its configured function inside SIMATIC TI 405.
Downstream Receiving channel, field device or operator interface.	Supervision Diagnostics, alarms and process indications confirm healthy operation.

Applications and operating context

COMMON APPLICATIONS

Installed-base maintenance Restore the assigned four-channel analog output module position without changing the surrounding system design.	Loop and channel service Retain terminal assignments, scaling and channel ownership during controlled replacement.
Fault isolation Separate module, field wiring and configuration causes during troubleshooting.	Commissioning Prove the complete signal path before returning the process to service.

OPERATIONAL WORKFLOW

Normal operation	405-4DAC-1 maintains the assigned four-channel analog output module path.
Inspection	Review physical condition, status and process indications.
Fault isolation	Separate field, connection, module and configuration causes.
Replacement	Match the complete identity and restore retained interfaces.
Commissioning	Prove static and dynamic response under controlled conditions.
Return to service	Remove bypasses after alarms and process behavior are accepted.

SERVICE PLANNING

People Controls, electrical and operations roles defined.	Information Marking, configuration and connection map available.
Hardware Correct replacement, tools and test equipment prepared.	Process Isolation, test and release windows approved.

Model-specific questions

FAQ

Where is Siemens 405-4DAC-1 used?	It is used in the SIMATIC TI 405 platform as a four-channel analog output module.
Which task is assigned to Siemens 405-4DAC-1?	The assigned task is four-channel analog output module.
What does current range mean for Siemens 405-4DAC-1?	Current range: 4 to 20 mA.
When installing Siemens 405-4DAC-1, which voltage ranges must be confirmed?	Confirm 0 to 5 V; 0 to 10 V.
How should the system family for Siemens 405-4DAC-1 be recorded?	Record the applicable value as SIMATIC TI 405.
Which connection control can distinguish Siemens 405-4DAC-1 from a nearby execution?	Use Match installed terminals together with the complete model marking.
What functional test completes Siemens 405-4DAC-1 commissioning?	Exercise the assigned four-channel analog output module path and verify the expected system response.
Why should Siemens 405-4DAC-1 keep its complete suffix or alternate identifier?	The complete marking separates this execution from nearby variants with different interfaces or ranges.

MAINTENANCE DECISIONS

Keep in service	Status and end-to-end response remain stable.
Investigate	Intermittent value, diagnostic or connector condition appears.
Replace	Confirmed product fault persists after field and configuration checks.
Escalate	Identity, compatibility or process consequence remains unclear.

SUCCESSFUL OUTCOME

Identity Exact model and installed position agree.	Connections Every assigned interface is restored.
Configuration All retained settings are active.	Response The process and diagnostic path pass testing.

Precautions and selection

EIGHT PRODUCT PRECAUTIONS

1	Confirm the complete Siemens 405-4DAC-1 marking before removal.
2	Place the affected SIMATIC TI 405 function in its approved maintenance state.
3	Record terminals, connectors and installed orientation before disconnection.
4	Retain channel assignments, scaling and communication settings.
5	Inspect mating contacts and terminal hardware for damage or contamination.
6	Restore shields, commons and protective grounding exactly as assigned.
7	Energize under controlled conditions and review module status.
8	Verify the end-to-end process response before release.

RELATED SIEMENS PRODUCT PAGES

Siemens 6GK1905-0AE00	https://www.apterpower.com/Siemens/Siemens-Simatic-Net/6gk1905-0ae00
Siemens 6DR2410-4	https://www.apterpower.com/Siemens/Siemens-Sipart/6dr2410-4

FINAL PRODUCT SUMMARY

Model	405-4DAC-1
Family	SIMATIC TI 405
Function	four-channel analog output module
Selection basis	Complete identity, interfaces and configured function
Installation basis	Saved connections and controlled configuration
Release basis	Verified mechanical, electrical, logical and process response