24701-28-05-XX-065-03-XX MOD:323933-00-02

01 / Product role and configuration

Confirm MOD — Match mechanical interface — Validate measurement chain

Product series	24701 probe housing assemblies
Modification identifier	323933-00-02
Base housing body material	303 stainless steel
Base sleeve material	304 stainless steel

Final mounting geometry and included items are controlled by the approved drawing and quotation.

An intermediate penetration provides access to a recessed target while keeping adjustment outside the casing. Plan the cable entry and sleeve withdrawal space as part of the installation.

Assembly identity

MOD 323933-00-02 remains part of the supplied identity; retain both XX positions.

Product and installation enquiries

sales13@apterpower.com | +86 18030235313

Apter Power guide - apply the approved assembly and site instructions.

24701-28-05-XX-065-03-XX MOD:323933-00-02

02 / Technical capability and interfaces

Standard penetration adjustment	+/-0.5 in (13 mm)
Long-sleeve support threshold	Combined standoff and penetration greater than 12 in (300 mm)
Probe lead relationship	Lead must be longer than the sleeve
Service access	External probe mounting and adjustment
Standard companion support	37948-01 probe support and oil seal; selected separately

These standard-family relationships require checking against the actual modified assembly.

Base-order probe option 28	3300 XL 8 mm probe with approval option
Base-order cable option 05	0.5 m (20 in)
Base-order penetration 065	6.5 in
Base-order fittings 03	One 3/4-14 NPT plug, one 3/4-14 to 1/2-14 NPT reducer and cable seal-grip kit

Mechanical versus electrical role

The housing provides mechanical support and external adjustment. Electrical performance comes from the installed proximity probe, matching cable, Proximitor sensor and monitor. A housing-family match alone does not establish channel compatibility.

Product and installation enquiries

sales13@apterpower.com | +86 18030235313

Apter Power guide - apply the approved assembly and site instructions.

24701-28-05-XX-065-03-XX
MOD:323933-00-02

03 / Integration and operating context

Radial shaft monitoring

Support a correctly matched proximity probe at a machine casing for radial shaft vibration measurement. The probe, cable, Proximitor sensor and monitor must form the intended measuring chain.

Axial position monitoring

Position a suitable proximity probe toward a conductive axial target. Check the final sleeve reach, mounting stiffness and usable probe gap before commissioning.

Installed chain

The housing provides mechanical support and external adjustment. Electrical performance comes from the installed proximity probe, matching cable, Proximitor sensor and monitor. A housing-family match alone does not establish channel compatibility.

Recessed-target alignment

The base penetration is 6.5 in. Check the sleeve axis, target clearance and complete C plus D reach against the machine drawing before adjusting the gap.

External probe maintenance

Access the sleeve from outside the machine. Record its position before removal and re-establish the operating gap and channel response after reinstallation.

MOD control

Compare the actual assembly to MOD 323933-00-02 before approving installation or replacement.

Product and installation enquiries

sales13@apterpower.com | +86 18030235313

Apter Power guide - apply the approved assembly and site instructions.

04 / Engineering decisions and precautions

Match the modification

Use the full 24701-28-05-XX-065-03-XX MOD:323933-00-02 identity. Verify the modification drawing, actual mounting thread and standoff arrangement before installation; XX must not be treated as a zero option.

Check reach and target clearance

The base penetration is 6.5 in. Check the sleeve axis, target clearance and complete C plus D reach against the machine drawing before adjusting the gap.

Support the complete sleeve

Evaluate the full standoff-plus-penetration reach. Provide support near the probe when the combined reach exceeds 12 in (300 mm); confirm the support and oil-seal arrangement through an inner bearing housing.

Route the probe cable

The base cable option is 0.5 m (20 in). Confirm the actual cable under MOD 323933-00-02, keep it longer than the sleeve and allow access without loading the connector.

Verify fittings and area suitability

The base fittings selection is one 3/4-14 npt plug, one 3/4-14 to 1/2-14 npt reducer and cable seal-grip kit. Match actual fittings and seals to the modified unit. The 24701 marking must not be treated as CA24701 explosion-proof certification.

Verify the measuring channel

Check probe identity, matched electrical components, target clearance and stable gap response. Confirm monitor scaling and the approved machine acceptance procedure before returning the channel to service.

Product and installation enquiries

sales13@apterpower.com | +86 18030235313

Apter Power guide - apply the approved assembly and site instructions.

24701-28-05-XX-065-03-XX MOD:323933-00-02

05 / Service review and related references

Offered-unit review

Request a legible complete model and MOD marking, housing-body and sleeve views, the probe identification and cable entry. Compare the mounting interface and modification drawing before approving a replacement.

Included items and channel boundary

The offered item is a housing assembly. Confirm the probe, sleeve, selected fittings, seals and accompanying documents item by item in the quotation. A Proximitor sensor, extension cable, monitor or compatible support is included only when expressly listed; confirm quantity and dispatch separately.

Technical basis

Bently Nevada 21000, 24701, and 164818 Proximity Probe Housing Assemblies, 141600 Rev. AC

Other Bently Nevada references

Bently Nevada 24701-28-05-05-064-03-02

Bently Nevada 21000-00-00-00-019-03-02

Bently Nevada 24701-00-00-00-290-03-02

Separate references only. Confirm compatibility and included items for the actual installation.

Product and installation enquiries

sales13@apterpower.com | +86 18030235313

Apter Power guide - apply the approved assembly and site instructions.