
# 3300 XL NSv Proximity Transducer System

## Datasheet

Cordant™

147385 Rev. R



## Description

The 3300 XL NSv Proximity Transducer system is intended for use with centrifugal air compressors, refrigeration compressors, process gas compressors, and other machines with tight installation requirements. The 3300 XL NSv Proximity Transducer System consists of:

- a 3300 NSv probe
- a 3300 NSv extension cable
- a 3300 XL NSv Proximitor Sensor(1)

The primary uses for the 3300 XL NSv Transducer System are for areas where counter bore, sideview, or rearview restrictions limit the use of standard Bently Nevada 3300 and 3300 XL 5 and 8 mm Transducer Systems. It is also ideal for small target applications, such as measuring radial vibration on shafts smaller than 51 mm (2 in) or axial position on flat targets smaller than 15 mm (0.6 in). It is primarily used in the following applications on fluid-filmed bearing machines where a small shaft or reduced side-view is present:

- Radial vibration and radial position measurements
- Axial (thrust) position measurements
- Tachometer and zero speed measurements
- Phase reference (Keyphasor signals)

The 3300 XL NSv Transducer System design allows it to replace both the 3300 RAM Transducer Systems and the 3000-series or 7000-series 190 Transducer System. Upgrades from the 3300 RAM system to the 3300 XL NSv system may use the existing probe, extension cable, and monitoring

Baker Hughes

system with 3300 XL NSv Proximitor Sensor. Upgrades from the 3000-series or 7000-series Transducer System must replace the probe, extension cable, and Proximitor Sensor with NSv components.

The 3300 XL NSv Transducer System has an Average Scale Factor of 7.87 V/mm (200 mV/mil), which is the most common output for eddy current transducers. Its enhanced side-view and small target characteristics give it a shorter linear range than the Bently Nevada 3300 XL-series 5 and 8 mm Transducer System. The 1.5 mm (60 mils) of linear range exceeds the linear range of the 3000-series 190 Transducer System.



Although the terminals and connector on the Proximitor Sensor have protection against electrostatic discharge, take reasonable precautions to avoid electrostatic discharge during handling.

## Proximitor Sensor

The 3300 XL NSv Proximitor Sensor has similar features to those found in the 3300 XL 8 mm Proximitor Sensor. Its thin design allows the user to mount it in either a high-density DIN-rail installation or a more traditional panel mount configuration. Improved RFI/EMI immunity allows the 3300 XL NSv Proximitor Sensor to achieve European CE mark approvals without any special mounting considerations. This RFI immunity also prevents nearby high frequency radio signals from adversely affecting the transducer system. SpringLoc terminal strips on the Proximitor Sensor require no special installation tools and facilitate faster, highly robust field wiring connections.

## Proximity Probe and Extension Cable

The 3300 NSv probe and extension cable are mechanically and electrically compatible and interchangeable with Bently Nevada's previous 3300 RAM proximity probe and extension cable. The NSv probe has increased chemical resistance compared to the 3300 RAM probe, which allows its use in many process compressor applications. The side-view characteristics of the 3300 NSv probe are also superior to those of the 3000-series 190 probe when gapping the 3300 NSv probe at the same distance from the probe target.

The 3300 NSv probe comes in varying probe case configurations, including armored and unarmored 1/4-28, 3/8-24, M8X1 and M10X1 probe threads. The reverse mount 3300 NSv probe comes standard with either 3/8-24 or M10X1 threads. All components of the transducer system have gold-plated brass ClickLoc connectors. ClickLoc connectors lock into place and prevent the connection from loosening. The patented TipLoc molding method provides a robust bond between the probe tip and the probe body. Bently Nevada's patented CableLoc design provides 220 N (50 lb) of pull strength and securely attaches the probe cable to the probe tip. Connector protectors are recommended for use on the probe-to-extension cable connection, as well as on the cable-to-Proximitor Sensor connection. Connector protectors prevent most liquids from entering into the ClickLoc connectors and adversely affecting the electrical signal(2).

Notes:

(1) Proximitor Sensors are supplied by default from the factory calibrated to AISI 4140 steel. Calibration to other target materials is available upon request.

(2) Silicone tape is also provided with each 3300 NSv extension cable and can be used instead of connector protectors. Silicone tape is not recommended in applications where the probe-to-extension cable connection will be exposed to turbine oil.

# Specifications

Unless otherwise noted, the following specifications are for a 3300 XL NSv Proximitor Sensor, extension cable and probe between 0°C and +45°C (+32°F to +113°F) at a maximum altitude of 2000 m, with a -24 Vdc power supply, a 10 kΩ load, a Bently Nevada supplied AISI 4140 steel target that is 31 mm (1.2 in) diameter or larger, and a probe gap of 1.0 mm (40 mils). The system accuracy and interchangeability specifications do not apply when using a transducer system calibrated to any target other than a Bently Nevada AISI 4140 steel target.

## Electrical

| | |
|---|---|
| Proximitor Sensor Input | Accepts one non-contacting 3300 RAM or 3300 NSv Proximity Probe and Extension Cable. |
| Power | Requires -17.5 Vdc to -26 Vdc without barriers at 12 mA maximum consumption, -23 Vdc to -26 Vdc with barriers. Operation at a more positive voltage than -23.5 Vdc can result in reduced linear range. |
| Supply Sensitivity | Less than 2 mV change in output voltage per volt change in input voltage. |
| Output resistance | 50 Ω |
| **Probe dc Resistance** | |
| Probe Length (m) | Resistance from the Center Conductor to the Outer Conductor ($R_{PROBE}$) (ohms) |
| 0.5 | 4.0 ± 0.5 |
| 1.0 | 4.2 ± 0.5 |
| 5.0 | 5.3 ± 0.7 |
| 7.0 | 5.9 ± 0.9 |
| Extension cable dc resistance | Center conductor: 0.220 Ω/m (0.067 Ω/ft)<br><br>Shield: 0.066 Ω/m (0.020 Ω/ft) |
| Extension cable capacitance | 69.9 pF/m (21.3 pF/ft) typical |
| Field Wiring | 0.2 to 1.5 mm² (16 to 24 AWG)[0.25 to 0.75 mm² (18 to 23 AWG) with ferrules]. Recommend using three-conductor shielded triad cable. Maximum length of 305 meters (1,000 feet) between the 3300 XL NSv Proximitor Sensor and the monitor. See the frequency response graphs Figure 16 and Figure 17 for signal rolloff at high frequencies when using longer field wiring lengths. |
| Linear Range | 1.5 mm (60 mils). Linear range begins at approximately 0.25 mm (10 mils) from target and is from 0.25 to 1.75 mm (10 to 70 mils) (approximately -1 to -13 Vdc). |
| Recommended Gap Setting | 1.0 mm (40 mils) |
| **System performance over ambient temperature range (0°C to 45°C)** | |
| Incremental Scale Factor (ISF) | 7.87 V/mm (200 mV/mil) +12.5%/-20% including interchangeability error when measured in increments of 0.25 mm (10 mils) over the 1.5 mm (60 mil) linear range. |
| Deviation from best fit straight line (DSL) | Less than ±0.06 mm (±2.3 mils). |

| | |
|---|---|
| Frequency Response | 0 to 10 kHz: +0, -3 dB typical, with up to 305 meters (1000 feet) of field wiring. |
| Target Size (flat target) | Minimum: 8.9 mm (0.35 in) diameter<br><br>Recommended minimum: 13 mm (0.5 in) diameter<br><br>Axial position measurements on shaft diameters smaller than 13 mm (0.5 in) will generally result in a change in scale factor. Reducing the gap between the probe and target will help limit the change in scale factor. See Figure 12 for additional information. |

| | |
|---|---|
| Shaft Diameter | Minimum (standard X-Y probe configuration): 30 mm (1.2 in)<br><br>Minimum (X-Y proximity probes offset axially by 23 mm [0.9 in]): 20 mm (0.8 in)<br><br>Measurements on shaft diameters smaller than 30 mm (1.2 in) usually require close spacing of radial vibration or axial position transducers. This creates the potential for their electromagnetic emitted fields to interact with one another (cross-talk), resulting in erroneous readings. To prevent cross-talk, maintain minimum separation of transducer tips of at least 25 mm (1.0 in) for axial position measurements or 23 mm (0.9 in) for radial vibration measurements. See Figure 14: Probe Cross-talk with Probes Mounted in Parallel and Figure 15: Probe Cross-talk with Probes Mounted in X-Y Configuration. Radial vibration or radial position measurements on shaft diameters smaller than 20 mm (0.8 in) will generally result in greater than a 10% change in Average Scale Factor (ASF). See Figure 13 for additional information. |

| | |
|---|---|
| Minimum Bend Radius (with or without sst armor) | 25.4 mm (1.0 in) |
| **System Weight (typical)** | |
| Probe | Approximately 14 to 150 g (0.5 to 5.3 oz) |
| Extension Cable | 45 g/m (0.5 oz/ft) |
| Armored Extension Cable | 64 g/m (0.7 oz/ft) |
| Proximitor Sensor | 255 g (9 oz) |

## Thread Engagement Limits

| Probe Case Thread | Maximum Length of Thread Engagement |
|---|---|
| **1/4-28** | 0.375 in |
| **3/8-24** | 0.563 in |
| **M8x1** | 12 mm |
| **M10x1** | 15 mm |

Maximum thread engagement lengths are per the industry standard of 1.5 times the nominal thread diameter. A fit class matching that of the external probe thread is assumed for all internal threads. Applications with thread engagement lengths exceeding the values in the table above may exhibit binding during installation. Contact your Bently Nevada representative if you require probe thread engagement lengths exceeding the values above. Bently Nevada does not replace proximity probes under warranty due to excessive thread engagement lengths.

When drilling and tapping a mounting hole **for a 1/4-28 probe**, a **#3 or larger tap drill** is recommended.

## Environmental Limits

| | |
|---|---|
| **Probe Temperature Range** | |
| Operating Temperature | -52°C to +177°C (-62°F to +351°F) |
| Storage Temperature | -52°C to +177°C (-62°F to +351°F)<br>Exposing the probe to temperatures below -34°C (-30°F) for a sustained period of time may cause premature failure of the pressure seal. |
| **Extension Cable Temperature Range** | |
| Operating and Storage Temperature | -52°C to +177°C (-62°F to +351°F) |
| **Proximitor Sensor Temperature Range** | |
| Operating Temperature | -52°C to +100°C (-62°F to +212°F) |
| Storage Temperature | -52°C to +105°C (-62°F to +221°F) |
| Relative Humidity | 100% condensing, non-submersible when connectors are protected.Tested to IEC 68-2-3 damp heat. |

| | |
|---|---|
| **05** | Multiple Approvals<br>For a shorter delivery time, order commonly stocked probes. Currently, stocked probes consist of the following part numbers: 330901-00-24-05-02-00, 330901-00-90-05-02-00, 330902-00-50-05-02-00, 330902-00-95-05-02-00, 330903-00-02-10-02-00, 330903-00-03-10-02-00, 330906-02-12-05-02-00. |

## 3300 XL NSv Proximitor Sensor

| **330980-AA-BB** | |
|---|---|
| **A: Total Length and Mounting Option** | |
| **50** | 5.0 meters (16.4 feet) system length, panel mount |
| **51** | 5.0 meters (16.4 feet) system length, DIN mount |
| **52** | 5.0 meters (16.4 feet) system length, no mounting hardware[1] |
| **70** | 7.0 meters (23.0 feet) system length, panel mount |
| **71** | 7.0 meters (23.0 feet) system length, DIN mount |
| **72** | 7.0 meters (23.0 feet) system length, no mounting hardware[1] |
| **B: Agency Approval Option** | |
| **00** | Not required |
| **05** | Multiple approvals |

## 3300 NSv Extension Cable

**330930-AAA-BB-CC**

Make sure that the extension cable length and the probe length, when added together, equal the Proximitor Sensor total length.

| **A: Cable Length Option** | |
|---|---|
| **040** | 4.0 meters (13.1 feet) |
| **045** | 4.5 meters (14.8 feet) |
| **060** | 6.0 meters (19.7 feet) |
| **065** | 6.5 meters (21.3 feet) |
| **B: Connector and Cable Option** | |
| **00** | Without stainless steel armor |
| **01** | With stainless steel armor, with FEP jacket |
| **02** | With stainless steel armor, without FEP jacket |
| **03** | Without stainless steel armor, with connector protector |
| **04** | With stainless steel armor, with FEP jacket, with connector protector |
| **05** | With stainless steel armor, without FEP jacket, with connector protector |
| **06** | FluidLoc cable without stainless steel armor |
| **07** | FluidLoc cable with stainless steel armor, with FEP jacket |
| **08** | FluidLoc cable with stainless steel armor, without FEP jacket |
| **09** | FluidLoc without stainless steel armor, with connector protector |

| | |
|---|---|
| **10** | FluidLoc cable with stainless steel armor, with FEP jacket, with connector protector |
| **11** | FluidLoc cable with stainless steel armor, without FEP jacket, with connector protector |
| **C: Agency Approval Option** | |
| **00** | Not Required |
| **05** | Multiple Approvals |

## Accessories

| | |
|---|---|
| 147357 | 3300 XL NSv Proximitor User Guide |
| 02120015 | Bulk field wire. 1.0 $mm^2$ (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet. |
| 138492-01 | Replacement panel-mount mounting pad |
| 138493-01 | Replacement DIN-mount mounting pad |
| 01609137 | BNC (F) to banana plugs |
| 01609138 | Proximitor Connector Test Pin wiring (two test pins to a BNC (F) connector) |
| 40971-04 | 50 Ω cable with two BNC (M) connectors. Use this cable in combination with adapter 01609137 and adapter 01609138 when checking performance of the transducer system from the Proximitor Sensor test pin holes. |
| 04310310 | 3300 XL Proximitor Sensor Panel-mount Screws. Package includes one 6-32 UNC thread forming mounting screw (supplied standard with 3300 XL Proximitor Housings [3300 XL option]). |
| 03200006 | Silicone self-fusing tape. A 9.1 meter (10 yard) roll of silicone tape to protect connectors. It is easy to install and provides excellent electrical isolation and protection from the environment. It is not recommended for use inside the casing of the machine. |
| 40113-03 | Connector Protector Kit for 3300 NSv probes and extension cables, including connector protectors and installation tools. |
| 136536-01 | Connector Protector Adapter. Allows connector protector installation tools manufactured prior to 1998 to be used with 75 Ω ClickLoc connectors. |
| 40180-03 | Connector Protectors. Package contains 10 pairs of connector protectors. |
| 03800000 | Male Connector Protector. Placed on the extension cable to connect to the female connector protector on the probe and provide environmental protection of connectors. |
| 03800001 | Female Connector Protector. Placed on the probe lead to connect to the male connector protector on the extension cable and provide environmental protection of connectors. Also placed on the extension cable to slide over the Proximitor Sensor connection and protect it from the environment. |
| 330153-05 | 3300 NSv Connector Kit. Used on 3300 NSv probes and extension cables. Contains one set of male and female ClickLoc connectors, sleeves and one strip of silicone tape. |