Bently Nevada 330101-00-32-10-01-00

Apter Power complete product information

Bently Nevada 330101-00-32-10-01-00 is a 3300 XL 8 mm proximity probe with a 3/8-24 UNF case thread, 1.0 m integral lead and clickloc connector with protector.

01 / Product role

This 3300 XL 8 mm probe senses the gap to a conductive target as one part of the complete proximity transducer chain.

Parameter	Selected configuration
Probe family	3300 XL 8 mm
Case thread	3/8-24 UNF
Lead armor	without armor
Unthreaded length	0 in

Installed-system context

Context	Verified use
Sensing-chain context	330101-00-32-10-01-00 is the probe at the machine target within a 3300 XL 8 mm probe, cable and Proximitor arrangement.
Application scope	Use the installed system calibration and target geometry to select a supported vibration, position or phase-reference location.

02 / Exact ordered configuration

Parameter	Selected configuration
Probe family	3300 XL 8 mm
Case thread	3/8-24 UNF
Lead armor	without armor
Unthreaded length	0 in
Overall case length	3.2 in
Probe lead length	1.0 m
Connector	ClickLoc connector with protector
Approval selection	no agency approval selected

Option relationship

Part prefix 330101 selects a 3/8-24 UNF case without lead armor. The selected unthreaded section is 0 in, within an overall 3.2 in case.

Option 10 provides a 1.0 m lead. Code 01 supplies a clickloc connector with protector; keep this connection clean and match it to the extension cable.

Technical reference: Bently Nevada 3300 XL 8 mm Proximity Transducer System, 141194 Rev. AN.

Apter Power technical support
sales13@apterpower.com | +86 18030235313

03 / Applications and compatibility

Documented uses

Use	Engineering context
Machine vibration	Observe a suitable shaft target for relative vibration in a documented transducer installation.
Axial position	Use an approved axial position arrangement with the correct target and probe gap.
Reference signal	Provide a phase or speed reference only where the monitoring channel and target support it.
Service replacement	Preserve the 3/8-24 UNF thread, 3.2 in case and 1.0 m lead when comparing the installed probe.

The final code 00 denotes no agency approval selected. Gap, scale factor and linear range describe the matched 3300 XL 8 mm system, rather than this probe alone.

Technical questions

Question	Engineering answer
What sensing family does 330101-00-32-10-01-00 belong to?	It is a 3300 XL 8 mm probe. It works with a matched extension cable and Proximitor sensor.
Which case thread is selected for 330101-00-32-10-01-00?	The 330101 part prefix selects a 3/8-24 UNF case thread.
Is the lead of 330101-00-32-10-01-00 armored?	No. The 330101 probe prefix denotes a version without lead armor.

04 / Installation precautions

Check	Action
Isolation	Make the measurement channel and machine safe before changing the probe.
Thread fit	Confirm the 3/8-24 UNF mount without forcing a different case thread.
Target clearance	Inspect the available target area and side-view clearance before setting the probe gap.
Cable routing	Keep the lead clear of sharp edges and protect the coaxial connector from contamination.
System length	Count the 1.0 m probe lead in the total length of the matched transducer chain.
Gap acceptance	Check the final DC gap voltage and dynamic signal under the approved site procedure.

Technical notes

Topic	Explanation
Probe configuration	330101 selects a 3/8-24 UNF unarmored case with 3.2 in overall length and 1.0 m lead.
System boundary	Measurement performance depends on the matched probe, extension cable, Proximitor sensor and target material.

Technical questions

Question	Engineering answer
How long is the unthreaded portion of 330101-00-32-10-01-00?	Option 00 selects 0 in unthreaded length.
What is the overall probe case length of 330101-00-32-10-01-00?	Option 32 selects 3.2 in overall case length.
How long is the integral lead on 330101-00-32-10-01-00?	Option 10 selects a 1.0 m probe lead.

05 / Supply and service reference

Question	Engineering answer
What connection is supplied with 330101-00-32-10-01-00?	Option 01 specifies a clickloc connector with protector; protect the connection during routing and installation.
Does 330101-00-32-10-01-00 alone establish the system measurement range?	No. The matched 3300 XL 8 mm probe, extension cable, Proximitor sensor and target calibration establish system performance.

Available unit

Bently Nevada 330101-00-32-10-01-00; Condition: New, original product. Confirm the probe and any separately supplied extension cable, sensor or connector accessories in the quotation.

Related product references

Related product	Selection note
Bently Nevada 330880-00-00-000-03-02	Separate catalogue reference
Bently Nevada 21504-000-040-10-02	Separate catalogue reference
Bently Nevada 330851-02-000-060-10-00-00	Separate catalogue reference
Bently Nevada 330851-02-000-030-10-00-00	Separate catalogue reference
Bently Nevada 330101-00-10-10-02-00	Separate catalogue reference
Bently Nevada 330101-00-20-10-02-00	Separate catalogue reference
Bently Nevada 330101-00-08-05-02-00	Separate catalogue reference
Bently Nevada 330801-28-20-050-03-02	Separate catalogue reference

Technical reference: Bently Nevada 3300 XL 8 mm Proximity Transducer System, 141194 Rev. AN.