DS200SDCCG5A

General Electric / Drive Control Card

Installation and commissioning checks for General Electric DS200SDCCG5A.

01 Identify the installed configuration

Before replacement, capture the full card marking, socketed-device identities, connector positions and existing drive parameters. Do not apply feature differences documented for other SDCC groups to this G5A execution without a matching manufacturer instruction.

02 Prepare the change

Record the complete marking, companion hardware and project settings before removing the installed item.

01 Read full label

Record DS200SDCCG5AHD or the actual offered-unit suffix.

02 Map socketed devices

Photograph each populated memory and configuration position.

03 Preserve drive settings

Export or record parameters before removing the original card.

03 Fit and configure

04 Track interconnects

Label ribbon and board connectors before release.

05 Avoid cross-group claims

Do not use G1/G3/G4-specific ratings for this G5A card.

06 Prove drive response

Follow the approved startup and functional test sequence.

Source and application boundary

GE board label DS200SDCCG5AHD in offered-unit photograph; GE SDCC drive-control card family.

G5A is the offered base code; HD is visible on the photographed board. Group 1/3/4 instruction data are not transferred to G5A.

Related product references

Separate product listings for project review; confirm each order code and system fit independently.

General Electric DS200CTBAG1ADD	General Electric IS215UCVEH2AE

Apter Power | Technical enquiry

sales13@apterpower.com | +86 18030235313

Send the complete model and installed-system details when requesting a quotation.