Hirschmann M-FAST SFP-MM/LC

INSTALLATION AND COMMISSIONING GUIDE / EXACT-MODEL ENGINEERING FILE

Hirschmann M-FAST SFP-MM/LC is identified as a multimode fast ethernet sfp transceiver for the Hirschmann Fast Ethernet SFP platform. The complete marking and installed interface arrangement must be matched together before replacement.

01 Job scope and safe-work boundary

This field guide organizes the work sequence for the exact offered reference. The site-approved isolation and maintenance procedure remains controlling.

Match the complete marking	Compare M-FAST SFP-MM/LC with the installed label and applicable Hirschmann documentation.
Check the offered item before ordering	Request photos of the offered M-FAST SFP-MM/LC and compare markings, interfaces and included items with the installed unit.

Optical interface
One 100 Mbit/s LC multimode link operates at 1310 nm.

Published reach
Up to 5 km on 50/125 µm fiber or 4 km on 62.5/125 µm fiber.

Diagnostics
Optical input power, output power and transceiver temperature are available.

Required work record

Nameplate record	Photograph the complete M-FAST SFP-MM/LC marking and any revision identifier.
Host record	Identify the exact installed position and functional ownership in Hirschmann Fast Ethernet SFP platform.
Connection record	Label every connector, cable and terminal before disturbing the installed assembly.
Configuration record	Archive applicable project, address, setting or fail-safe information before removal.
Acceptance record	Define the expected indication and controlled functional result before energization.

Related product navigation

ABB 3BHE036290R0005 GDC806 B05	Related product page; verify the complete installed model before selection.
ABB DFC02 DFC-02	Related product page; verify the complete installed model before selection.
ABB DO801 3BSE020510R1	Related product page; verify the complete installed model before selection.
ABB SCYC51220-63901075	Related product page; verify the complete installed model before selection.

02 Pre-installation readiness

Verify the complete identity	Check every token in M-FAST SFP-MM/LC against the offered label and approved record.
Isolate the work boundary	Follow the site procedure for stored energy, field power and electrostatic handling.
Record connections	Photograph and label carriers, terminals, cables and keying before removal.
Preserve configuration	Archive applicable Hirschmann Fast Ethernet SFP platform settings before replacement.
As-found evidence	Retain the complete label, installed position, connector map and current indications before removal.
Replacement boundary	Compare included carriers, terminals, cables and accessories with the quotation and installed scope.

Stop conditions

Identity mismatch
Stop if any complete-model token or revision marker differs.

Interface mismatch
Stop if keying, connector count or host position does not match.

Missing baseline
Stop if the installed configuration or cable map cannot be recovered.

Technical readiness data

Complete order code	M-FAST SFP-MM/LC
Equipment role	Multimode Fast Ethernet SFP Transceiver
System context	Hirschmann Fast Ethernet SFP platform
Part number	943865001
Interface	1 × 100 Mbit/s LC
Fiber	Multimode

Planning questions

How should M-FAST SFP-MM/LC be identified before a replacement is approved?	Compare every token in the complete marking, installed position and documented multimode fast ethernet sfp transceiver role. Confirm the physical label before approval.
What evidence should be retained before removing M-FAST SFP-MM/LC?	Record the mounting position, connected interfaces, status indications and current Hirschmann Fast Ethernet SFP platform configuration. Photograph the complete label before disconnection.
How should the interfaces for M-FAST SFP-MM/LC be checked during installation?	Map each connector, terminal and cable to the as-found record and applicable manufacturer documentation. Preserve keying and shielding arrangements.

03 Replacement sequence

01 Record	Capture marking, position, connections, settings and current indications.
02 Isolate	Apply the approved energy-isolation and ESD procedure for the installed system.
03 Compare	Check the offered unit, included items and interface execution against the removed unit.
04 Fit	Install without forcing connectors; restore routing, shielding and keying from the record.
05 Configure	Restore only the approved settings, project data or fail-safe behavior that applies.
06 Prove	Run the product-specific commissioning checks and retain the results.

Product-specific installation focus

Installed-system replacement	Compare the exact code, host position and connected interfaces with the removed item.
Planned maintenance	Capture the as-found label, status and configuration before disturbing the installation.
Controlled commissioning	Restore documented connections and prove the intended signal, communication or control response.
Spare qualification	Keep revision, configuration and acceptance evidence with the spare-part record.

Connection restoration controls

Position	Restore the documented host position for M-FAST SFP-MM/LC.
Orientation	Use the as-found orientation and keying; do not force a connector or carrier.
Cable ownership	Reconnect each labeled path to its original documented interface.
Settings	Restore only the approved address, project, fail-safe or hardware settings that apply.
Inspection	Complete a visual and continuity review before controlled energization.

Field decision notes

Evidence scope	The official exact-part data sheet states the interface, optical reaches, diagnostics, power and environmental values.
Installation boundary	The exact installed carrier, terminals, cables and project configuration remain site-specific.
Technical reference	Belden Hirschmann M-FAST SFP-MM/LC technical data sheet

04 Commissioning and acceptance

Physical path	Confirm supported host position, optical medium, connector cleanliness and link partner.
Link state	Observe the port indication before and after the approved connection is made.
Traffic proof	Use the host diagnostics to prove the intended data path, not only optical link.
As-left record	Retain slot, transceiver type, fiber path and final diagnostic state.

Enquiry-to-dispatch record

Review your reference	Send the complete M-FAST SFP-MM/LC marking, quantity and installed-system context.
Confirm the offer	Review the offered identity, condition, included items and delivery details.
Arrange dispatch	Confirm the accepted quantity and destination in the quotation.

Applicable technical data

Wavelength	1310 nm
50/125 µm distance	0-5000 m
62.5/125 µm distance	0-4000 m
Power consumption	1 W
Diagnostics	Optical input/output power and temperature
Protection class	IP20

Result record matrix

Baseline	Record the pre-test state for M-FAST SFP-MM/LC and its host position.
Stimulus	Apply only the approved controlled command, signal or diagnostic action.
Observation	Capture module indication, host diagnostic and field response together.
Comparison	Compare the result with the approved system record, not a generic family expectation.
Disposition	Accept, correct and retest, or record the exception with its owner.

Acceptance boundary

Commissioning should progress from identity and connection checks to controlled power-up, diagnostics and functional proof. Keep the final status, test conditions and open exceptions in the handover record.

05 Fault isolation and handover

How can a suspected M-FAST SFP-MM/LC fault be separated from wiring or carrier faults?	Verify supply and reference conditions, then inspect mating hardware and external wiring. Use controlled substitution only after both signal paths are documented.
What should be verified after fitting M-FAST SFP-MM/LC?	Confirm normal indications, communication or signal continuity and the intended controlled-system response under an approved test state.
Can M-FAST SFP-MM/LC be replaced by a similar-looking assembly?	No direct equivalence is established by appearance. Compare the complete code, revision, interface execution and installed configuration.
What handover record is appropriate after work on M-FAST SFP-MM/LC?	Retain offered and removed markings, connection photographs, configuration evidence, diagnostics, functional-test results and unresolved exceptions.

Handover pack

Identity evidence
Offered and removed markings plus installed position.

Configuration evidence
As-found and as-left settings or project record.

Test evidence
Diagnostics, controlled functional results and open exceptions.

Close-out checks

Identity closed	The as-left record names M-FAST SFP-MM/LC without a shortened family reference.
Interfaces closed	Every restored connection is traceable to the pre-work record.
Function closed	The intended multimode fast ethernet sfp transceiver role has a recorded controlled-test result.
Exceptions closed	Outstanding diagnostic, configuration or scope exceptions have an owner and action.

Related product references

Hirschmann M4-FAST-8-SFP	Related product page; verify the complete installed model before selection.
OPTILOGTC OL2109	Related product page; verify the complete installed model before selection.
General Electric DS200IMCPG1CGC	Related product page; verify the complete installed model before selection.
Bently Nevada 3300/47	Related product page; verify the complete installed model before selection.
ABB 1KHL178025R0102P-COM02	Related product page; verify the complete installed model before selection.

Discuss the complete M-FAST SFP-MM/LC marking and installed configuration.
sales13@apterpower.com | +86 18030235313
Scan the WhatsApp QR to share nameplate and installed-system evidence.