ABB DFC02 DFC-02

INSTALLATION AND COMMISSIONING GUIDE / EXACT-MODEL ENGINEERING FILE

ABB DFC02 DFC-02 is identified as a freelance controller for the ABB Freelance DCS. The complete marking and installed interface arrangement must be matched together before replacement.

01 Job scope and safe-work boundary

This field guide organizes the work sequence for the exact offered reference. The site-approved isolation and maintenance procedure remains controlling.

Match the complete marking	Compare DFC02 DFC-02 with the installed label and applicable ABB documentation.
Check the offered item before ordering	Request photos of the offered DFC02 DFC-02 and compare markings, interfaces and included items with the installed unit.

Controller family
DFC02 DFC-02 belongs to the DFC 01/02 controller family in Freelance.

Engineering context
Freelance Engineering supports the DFC 01/02 controller family.

Telecontrol boundary
IEC 60870-5-104 is not released for DFC 01/02 in the cited ABB catalog.

Required work record

Nameplate record	Photograph the complete DFC02 DFC-02 marking and any revision identifier.
Host record	Identify the exact installed position and functional ownership in ABB Freelance DCS.
Connection record	Label every connector, cable and terminal before disturbing the installed assembly.
Configuration record	Archive applicable project, address, setting or fail-safe information before removal.
Acceptance record	Define the expected indication and controlled functional result before energization.

Related product navigation

ABB 3BHE036290R0005 GDC806 B05	Related product page; verify the complete installed model before selection.
ABB DO801 3BSE020510R1	Related product page; verify the complete installed model before selection.
ABB SCYC51220-63901075	Related product page; verify the complete installed model before selection.
Hirschmann M4-FAST-8-SFP	Related product page; verify the complete installed model before selection.

02 Pre-installation readiness

Verify the complete identity	Check every token in DFC02 DFC-02 against the offered label and approved record.
Isolate the work boundary	Follow the site procedure for stored energy, field power and electrostatic handling.
Record connections	Photograph and label carriers, terminals, cables and keying before removal.
Preserve configuration	Archive applicable ABB Freelance DCS settings before replacement.
As-found evidence	Retain the complete label, installed position, connector map and current indications before removal.
Replacement boundary	Compare included carriers, terminals, cables and accessories with the quotation and installed scope.

Stop conditions

Identity mismatch
Stop if any complete-model token or revision marker differs.

Interface mismatch
Stop if keying, connector count or host position does not match.

Missing baseline
Stop if the installed configuration or cable map cannot be recovered.

Technical readiness data

Complete order code	DFC02 DFC-02
Equipment role	Freelance Controller
System context	ABB Freelance DCS
Controller family	DFC 01/02
Engineering context	Supported by Freelance engineering
Telecontrol boundary	IEC 60870-5-104 is not released for DFC 01/02 in current ABB catalog

Planning questions

How should DFC02 DFC-02 be identified before a replacement is approved?	Compare every token in the complete marking, installed position and documented freelance controller role. Confirm the physical label before approval.
What evidence should be retained before removing DFC02 DFC-02?	Record the mounting position, connected interfaces, status indications and current ABB Freelance DCS configuration. Photograph the complete label before disconnection.
How should the interfaces for DFC02 DFC-02 be checked during installation?	Map each connector, terminal and cable to the as-found record and applicable manufacturer documentation. Preserve keying and shielding arrangements.

03 Replacement sequence

01 Record	Capture marking, position, connections, settings and current indications.
02 Isolate	Apply the approved energy-isolation and ESD procedure for the installed system.
03 Compare	Check the offered unit, included items and interface execution against the removed unit.
04 Fit	Install without forcing connectors; restore routing, shielding and keying from the record.
05 Configure	Restore only the approved settings, project data or fail-safe behavior that applies.
06 Prove	Run the product-specific commissioning checks and retain the results.

Product-specific installation focus

Installed-system replacement	Compare the exact code, host position and connected interfaces with the removed item.
Planned maintenance	Capture the as-found label, status and configuration before disturbing the installation.
Controlled commissioning	Restore documented connections and prove the intended signal, communication or control response.
Spare qualification	Keep revision, configuration and acceptance evidence with the spare-part record.

Connection restoration controls

Position	Restore the documented host position for DFC02 DFC-02.
Orientation	Use the as-found orientation and keying; do not force a connector or carrier.
Cable ownership	Reconnect each labeled path to its original documented interface.
Settings	Restore only the approved address, project, fail-safe or hardware settings that apply.
Inspection	Complete a visual and continuity review before controlled energization.

Field decision notes

Evidence scope	ABB documentation identifies DFC 01/02 as a Freelance controller family and defines current engineering and telecontrol boundaries.
Installation boundary	The exact installed carrier, terminals, cables and project configuration remain site-specific.
Technical reference	ABB Freelance DCS Product Catalog 3BDD015188

04 Commissioning and acceptance

Project archive	Secure the approved Freelance project and controller identity before replacement.
Interface record	Preserve connected I/O, network and serial paths with their configured ownership.
Controlled start	Restore configuration and prove controller state before enabling process commands.
Acceptance	Compare live indications and controlled functions with the pre-work baseline.

Enquiry-to-dispatch record

Review your reference	Send the complete DFC02 DFC-02 marking, quantity and installed-system context.
Confirm the offer	Review the offered identity, condition, included items and delivery details.
Arrange dispatch	Confirm the accepted quantity and destination in the quotation.

Applicable technical data

Engineering license scope	Freelance Engineering supports DCP 02/10 and DFC 01/02
Telecontrol protocols	IEC 60870-5-101/-104 option; -104 excluded for DFC 01/02

Result record matrix

Baseline	Record the pre-test state for DFC02 DFC-02 and its host position.
Stimulus	Apply only the approved controlled command, signal or diagnostic action.
Observation	Capture module indication, host diagnostic and field response together.
Comparison	Compare the result with the approved system record, not a generic family expectation.
Disposition	Accept, correct and retest, or record the exception with its owner.

Acceptance boundary

Commissioning should progress from identity and connection checks to controlled power-up, diagnostics and functional proof. Keep the final status, test conditions and open exceptions in the handover record.

05 Fault isolation and handover

How can a suspected DFC02 DFC-02 fault be separated from wiring or carrier faults?	Verify supply and reference conditions, then inspect mating hardware and external wiring. Use controlled substitution only after both signal paths are documented.
What should be verified after fitting DFC02 DFC-02?	Confirm normal indications, communication or signal continuity and the intended controlled-system response under an approved test state.
Can DFC02 DFC-02 be replaced by a similar-looking assembly?	No direct equivalence is established by appearance. Compare the complete code, revision, interface execution and installed configuration.
What handover record is appropriate after work on DFC02 DFC-02?	Retain offered and removed markings, connection photographs, configuration evidence, diagnostics, functional-test results and unresolved exceptions.

Handover pack

Identity evidence
Offered and removed markings plus installed position.

Configuration evidence
As-found and as-left settings or project record.

Test evidence
Diagnostics, controlled functional results and open exceptions.

Close-out checks

Identity closed	The as-left record names DFC02 DFC-02 without a shortened family reference.
Interfaces closed	Every restored connection is traceable to the pre-work record.
Function closed	The intended freelance controller role has a recorded controlled-test result.
Exceptions closed	Outstanding diagnostic, configuration or scope exceptions have an owner and action.

Related product references

Hirschmann M-FAST SFP-MM/LC	Related product page; verify the complete installed model before selection.
OPTILOGTC OL2109	Related product page; verify the complete installed model before selection.
General Electric DS200IMCPG1CGC	Related product page; verify the complete installed model before selection.
Bently Nevada 3300/47	Related product page; verify the complete installed model before selection.
ABB 1KHL178025R0102P-COM02	Related product page; verify the complete installed model before selection.

Discuss the complete DFC02 DFC-02 marking and installed configuration.
sales13@apterpower.com | +86 18030235313
Scan the WhatsApp QR to share nameplate and installed-system evidence.