HMS M00279-3266-140

INSTALLATION & COMMISSIONING GUIDE / EXACT-MODEL ENGINEERING FILE

HMS M00279-3266-140 is identified as a anybus communication module for the HMS Anybus industrial-network interface platform. The complete marking and installed interface arrangement must be matched before replacement.

01 Job scope and safe-work boundary

Offered assembly	HMS M00279-3266-140
Installed system	HMS Anybus industrial-network interface platform
Work boundary	Follow the site procedure for stored energy, field power and electrostatic handling.
As-found record	Send the complete M00279-3266-140 marking, quantity and installed-system context.

Readiness controls

Verify the complete identity
Check every token in M00279-3266-140 against the offered label and approved record.

Isolate the work boundary
Follow the site procedure for stored energy, field power and electrostatic handling.

Record connections
Photograph and label carriers, terminals, cables and keying before removal.

Preserve configuration
Archive applicable HMS Anybus industrial-network interface platform settings before replacement.

Related product references

- Fanuc A20B-3300-0281/04B
- General Electric IC695PNC001
- General Electric DS200TBCAG1AAB
- Hardy 1746-WS
- HMS AB5030-B
- ABB DO801 3BSE020510R1
- Bently Nevada 3300/47
- B&R 8V1022.001-2

Engineering record prompts

Connector record	Photograph every used connector, cable label, keying feature and shield termination.
Host record	Identify the carrier, rack, drive, chassis or operator station that owns the installed position.
Configuration record	Archive the applicable project, address, parameter, firmware or hardware-setting evidence.

02 Replacement sequence

01 Record	Send the complete M00279-3266-140 marking, quantity and installed-system context.
02 Verify	Compare M00279-3266-140 with the installed label and applicable HMS documentation.
03 Isolate	Follow the site procedure for stored energy, field power and electrostatic handling.
04 Compare	Check connectors, terminal blocks, carriers and cable condition before blaming the module.
05 Reconnect	Photograph and label carriers, terminals, cables and keying before removal.
06 Configure	Archive applicable HMS Anybus industrial-network interface platform settings before replacement.
07 Prove	Use an approved functional test and retain as-left diagnostic and acceptance evidence.
08 Handover	Retain the offered and removed M00279-3266-140 markings, connection photographs, configuration evidence, diagnostics, functional-test results and open exceptions.

Stop conditions

Identity mismatch
Stop if any complete-model token or revision marker differs.

Interface mismatch
Stop if keying, connector count or installed position does not match.

Missing baseline
Stop if the installed configuration or cable map cannot be recovered.

Related product references

- General Electric IC695PNC001
- General Electric DS200TBCAG1AAB
- Hardy 1746-WS
- HMS AB5030-B
- ABB DO801 3BSE020510R1
- Bently Nevada 3300/47
- B&R 8V1022.001-2
- Fanuc A20B-3300-0281/04B

Engineering record prompts

Host record	Identify the carrier, rack, drive, chassis or operator station that owns the installed position.
Configuration record	Archive the applicable project, address, parameter, firmware or hardware-setting evidence.
Supply-scope record	List terminal blocks, carriers, plugs, cables and accessories separately in the quotation.
Baseline result	Record initial indications, diagnostics and the controlled-system condition before work.
Identity decision	Approve only the complete order code and observed execution; do not shorten the family name.

03 Interface restoration and application fit

Complete identity	Use M00279-3266-140 as one complete reference in the quotation, service record and acceptance file.
Installed position	Record the exact host position and functional ownership within the HMS Anybus industrial-network interface platform.
Physical execution	Compare artwork, connectors, keying, terminal hardware and orientation with the removed assembly.
Configuration boundary	Preserve the applicable project, address, firmware or hardware-setting record before removal.
Acceptance evidence	Retain initial and as-left diagnostics plus the controlled functional-test result.
Unstated values	Do not assign electrical or compatibility values that are not established by the exact-model evidence.

Application acceptance

Installed-system replacement
Compare the exact code, host position and connected interfaces with the removed item.

Planned maintenance
Capture the as-found label, indications and configuration before disturbing the installation.

Controlled commissioning
Restore documented connections and prove the intended signal, communication or control response.

Spare qualification
Keep revision, configuration and acceptance evidence with the spare-part record.

Applicable technical data

Complete order code	M00279-3266-140
Product type	Anybus Communication Module
System context	HMS Anybus industrial-network interface platform
Complete module reference	M00279-3266-140
Product family	Anybus communication module
Verification boundary	Match host connector, network interface, board revision and installed configuration

Related product references

Hardy 1746-WS

HMS AB5030-B

ABB DO801 3BSE020510R1

Bently Nevada 3300/47

B&R 8V1022.001-2

Fanuc A20B-3300-0281/04B

04 Commissioning and fault isolation

Identity	Confirm the complete marking, artwork and installed position.
Interface map	Restore connectors and cables only from the approved as-found record.
Controlled power-up	Observe host and unit indications before enabling the process function.
Functional proof	Test the intended anybus communication module role and retain diagnostics with the handover.

Diagnostic questions

What configuration boundary matters when commissioning M00279-3266-140?	Use the approved HMS Anybus industrial-network interface platform configuration for M00279-3266-140. Physical fit alone does not establish electrical, firmware or project equivalence.
How can a suspected M00279-3266-140 fault be separated from an external fault?	Check host power, mating hardware, field wiring and the applicable signal or communication path before controlled substitution of M00279-3266-140.
What should be verified after installing M00279-3266-140?	Confirm normal indications, interface continuity and the intended anybus communication module response for M00279-3266-140 in an approved test state.
Can M00279-3266-140 be replaced by a similar-looking unit?	Appearance is not an equivalence criterion for M00279-3266-140; compare the complete order code, revision, connectors and installed configuration.

Result record matrix

Baseline	Record the pre-test state and host position.
Stimulus	Apply only the approved command, signal or diagnostic action.
Observation	Capture unit indication, host diagnostic and field response together.
Disposition	Accept, correct and retest, or record the exception with its owner.

Related product references

B&R 8V1022.001-2
Fanuc A20B-3300-0281/04B
General Electric IC695PNC001
General Electric DS200TBCAG1AAB
Hardy 1746-WS
HMS AB5030-B
ABB DO801 3BSE020510R1
Bently Nevada 3300/47

Engineering record prompts

Nameplate record	Capture the complete marking, visible revision and installed position before removal.

05 Handover and service record

Identity evidence
Offered and removed markings plus installed position.

Configuration evidence
As-found and as-left project, address or setting record.

Test evidence
Diagnostics, controlled functional result and open exceptions.

Supply evidence
Included items and separately supplied accessories confirmed in the quotation.

Close-out checks

Identity closed	The as-left record names M00279-3266-140 without a shortened family reference.
Interfaces closed	Every restored connection is traceable to the pre-work record.
Function closed	The intended anybus communication module role has a recorded controlled-test result.
Exceptions closed	Outstanding issues have an owner and documented action.

Ordering checks

Match the complete marking	Compare M00279-3266-140 with the installed label and applicable HMS documentation.
Check the offered item before ordering	Request photos of the offered M00279-3266-140 and compare markings, interfaces and included items with the installed unit.

Related product references

HMS AB5030-B

ABB DO801 3BSE020510R1

Bently Nevada 3300/47

B&R 8V1022.001-2

Fanuc A20B-3300-0281/04B

General Electric IC695PNC001

General Electric DS200TBCAG1AAB

Hardy 1746-WS

Engineering record prompts

Baseline result	Record initial indications, diagnostics and the controlled-system condition before work.
Identity decision	Approve only the complete order code and observed execution; do not shorten the family name.
Interface decision	Confirm connector count, orientation, pin ownership and field wiring against the as-found map.

Discuss the complete M00279-3266-140 marking with Apter Power.

sales13@apterpower.com | +86 18030235313

Scan the WhatsApp QR to share nameplate and installed-system evidence.