Electrodynamic Velocity Sensor

Mechanical velocity sensor for absolute vibration measurement of critical turbomachinery applications such as steam, gas and hydro turbines, compressors, pumps and fans to measure case vibration.





Sensor Orientation	
PR9268/01x-x00	Omni Directional
PR9268/20x-x00 PR9268/60x-000	Vertical, ± 30° (without sinking current) Vertical, ± 60° (with sinking current)
PR9268/30x-x00 PR9268/70x-000	Horizontal, ± 10° (without lifting/sinking current) Horizontal, ± 30° (with lifting/sinking current)
Dynamic Performance (PR9268/01x-x00)	
Sensitivity	17.5 mV/mm/s
Frequency Range	14 to 1000Hz
Natural Frequency	14Hz ± 7% @ 20°C (68°F)
Transverse Sensitivity	< 0.1 @ 80Hz
Vibration Amplitude	500µm peak-peak
Amplitude Linearity	< 2%
Maximum Acceleration	10g (98.1 m/s2) peak-peak continuous 20g (196.2 m/s2) peak-peak intermittent
Maximum Transverse Acceleration	2g (19.62 m/s2)
Damping Factor	~0.6% @ 20°C (68°F)
Resistance	1723Ω ± 2%
Inductance	≤ 90 mH
Active Capacity	< 1.2 nF

Dynamic Performance (PR9268/20x-x00 & PR9268/30x-x00)	
Sensitivity	28.5 mV/mm/s (723.9 mV/in/s)
Frequency Range	4 to 1000Hz
Natural Frequency	4.5Hz ± 0.75Hz @ 20°C (68°F)
Transverse Sensitivity	0.13 (PR9268/20x-x00) @ 110Hz 0.27 (PR9268/30x-x00) @ 110Hz
Vibration Amplitude (Mechanical Limit)	3000µm (4000µm) peak-peak
Amplitude Linearity	< 2%
Maximum Acceleration	10g (98.1 m/s2) peak-peak continuous 20g (196.2 m/s2) peak-peak intermittent
Maximum Transverse Acceleration	2g (19.62 m/s2)
Damping Factor	~0.56 @ 20°C (68°F) ~0.42 @ 100°C (212°F)
Resistance	1875Ω ± 10%
Inductance	≤ 90 mH
Active Capacity	< 1.2 nF
Dynamic Performance (PR9268/60x-000 & PR9268/70x-000)	
Sensitivity	22.0 mV/mm/s ± 5% @ Pin 3, 100Ω load 16.7 mV/mm/s ± 5% @ Pin 1, 50Ω load 16.7 mV/mm/s ± 5% @ Pin 4, 20Ω load
Frequency Range	10 to 1000Hz
Natural Frequency	8Hz ± 1.5Hz @ 20°C (68°F)
Transverse Sensitivity	0.10 @ 80Hz
Vibration Amplitude (Mechanical Limit)	3000µm (4000µm) peak-peak
Amplitude Linearity	< 2%
Maximum Acceleration	10g (98.1 m/s2) peak-peak continuous 20g (196.2 m/s2) peak-peak intermittent
Maximum Transverse Acceleration	2g (19.62 m/s2)
Damping Factor	~0.7 @ 20°C (68°F) ~0.5 @ 200°C (392°F)
Resistance	3270Ω ± 10% @ Pin 3 3770Ω ± 10% @ Pin 1
Inductance	≤ 160 mH
Active Capacity	Insignificant

Environmental, General		
Power	Self-Powered	
Operating Temperature Range	PR9268/01x-x00 PR9268/20x-x00 PR9268/30x-x00	-20 to +100°C (-4 to 212°F)
	PR9268/60x-000 PR9268/70x-000	-20 to +200°C (-4 to 392°F)
Protection Class	PR9268/20x-x00 PR9268/30x-x00	IP55
	PR9268/01x-x00 PR9268/60x-000 PR9268/70x-000	IP65
Relative Humidity	0 to 100%, Non Condensing	
Material	PR9268/20x-x00 PR9268/30x-x00	Al Mg Si Pb F 28
	PR9268/01x-x00 PR9268/60x-000 PR9268/70x-000	Stainless Steel
	Cable	PTFE, 3x 0.5mm2
	Armor	Stainless Steel
	Harting Plug	Die Cast Aluminium
Weight	PR9268/01x-x00	280g (without cable)
	PR9268/20x-x00 PR9268/30x-x00	930g
	PR9268/60x-000 PR9268/70x-000	1050g

Ordering Information

Model No.	/	Measurement Type XX	Cable X	-	Cable End X	0	0
PR9268		**01** Omni Directional **20** Vertical **30** Horizontal **60** Vertical HT **70** Horizontal HT	**0** 3m, Armored **1** 5m, Armored **2** 8m, Armored **3** 10m, Armored **4** 3m, Non-Armored **5** 5m, Non-Armored **6** 8m, Non-Armored **7** 10m, Non-Armored **8** No Cable*		**0** Harting Plug **1** Open Cab. End** **9** C-5015 Plug***		

*No Cable is only available, if "Omni Directional" Sensor is chosen.
**Open Cable End is not available for "HT" versions.
***C-5015 Plug is only available, if "No Cable" is chosen.

Special Versions

Part Number	Description
PR9268/20x-100-OPR PR9268/30x-100-OPR	Sensor option with FEP covered stainless steel armor.
PR9268/61x-100-CNSPEC PR9268/71x-100-CNSPEC	Sensor option with open cable end (Resistor Network to be installed separately).

Product Accessories

Product Description	Model Number
Extension Cable for PR9268/018-900 (see individual specsheet for details)	AC100